Specifications



Photo is representative





Eaton RES-40

Eaton Bussmann series RES fuse, time lag, non current-limiting, Industrial and commercial structures, 40 A, Class H, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 250 Vac, Standard, 10, 600 V

General specifications	
PRODUCT NAME	Eaton Bussmann series RES fuse
CATALOG NUMBER	RES-40
UPC	051712110402
EAN	5027590243995
PRODUCT LENGTH/DEPTH	0.78 in
PRODUCT HEIGHT	5.5 in
PRODUCT WIDTH	0.78 in
PRODUCT WEIGHT	0.29 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
PRODUCT TYPE	Fuse

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	40 A
INTERRUPT RATING	10 kAIC at 250 Vac
VOLTAGE RATING	600 V

Physical details

PACKAGING TYPE	Standard

General information

CLASS	Class H
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
QUANTITY	10
SPECIAL FEATURES	Super lag, time lag, non current-limiting

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 RES-40~SUPER LAG RENEWABLE FUSE 40/600
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RES-40

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.