Product specifications

Eaton C10M1

Catalog Number: C10M1

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 1 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C10M1

Model Code
CYLINDRICAL FUSE 10 x 38 1A AM 500V AC

UPC
051712754538

EAN
5027590493628

Product Length/Depth
38 mm

Product Height
10 mm

Product Width
10 mm

Product Weight
8.2 g

Warranty
1 year limited

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

fuse

Application

motor protection
for industrial applications

Amperage Rating

1 A

Fuse size

10 x 38 mm

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

500 V

Class

Class aM

Fuse type

C10M

Utilization category

aM (switchgear protection)

Fuse indicator

Other

Watt losses

0.1 W

Connection

Ferrule end x ferrule end

Construction size

10 mm x 38 mm

Fuse shape

Resources

Catalogs

CA134002EN

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Bussmann series complete full line catalog no. 1007

Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Cylindrical

Voltage type

AC

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Quantity

10

Voltage rating

500 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia