Product specifications

Eaton C14M10

Catalog Number: C14M10

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 10 Amps, 80 kA Breaking capacity, class aM, without indicator, compatible with a CH14 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C14M10

Model Code
CYLINDRICAL FUSE 14 x 51 10A AM 690V AC

UPC
051712754675

EAN
5027590494342

Product Length/Depth
51 mm

Product Height
14.3 mm

Product Width
14.3 mm

Product Weight
20.5 g

Compliances
GoST-R
RoHS Compliant
CE Marked

Certifications
IEC 60269

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

fuse

Application

motor protection
for industrial applications

Amperage Rating

10 A

Fuse size

14 x 51 mm

Current type

AC

Breaking capacity

80 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated voltage AC

690 V

Class

Class aM

Fuse type

C14M

Utilization category

aM (switchgear protection)

Fuse indicator

Other

Watt losses

0.53 W

Connection

Ferrule end x ferrule end

Construction size

14 mm x 51 mm

Fuse shape

Resources

Catalogs

CA134002EN

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Bussmann series complete full line catalog no. 1007

Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Cylindrical

Voltage type

AC

Suitable for

CH14 Modular fuse holder

Material

Ceramic

Mounting method

14 x 51 mm CH Modular fuse holder

Packaging type

Standard

Release characteristic

Other

Quantity

10

Voltage rating

690 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia