Specifications



Photo is representative





Eaton BK/GMA-1.5-R

Eaton GMA Series Fast-acting fuse 1.50A, 250 Vac, 32 Vdc (self certified), BK-GMA-1-5-R

General specifications	
PRODUCT NAME	Eaton Bussmann series GMA Fast-acting glass tube fuse
CATALOG NUMBER	BK/GMA-1.5-R
UPC	051712647175
PRODUCT HEIGHT	20 mm
PRODUCT DIAMETER	5.2 mm
PRODUCT WEIGHT	0.7 g
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
PRODUCT TYPE	5 x 20 mm Fast-acting glass tube fuse

Powering Business Worldwide

Product specifications

USED WITH	out axial leads
AMPERAGE RATING	1.50 A
INTERRUPT RATING	10 kAIC at 125 Vac 0.1 kAIC at 250 Vac
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	60 min at 135%, 2 min at 200%
MATERIAL	Glass tube Nickel-plated brass end cap construction
QUANTITY	100
VOLTAGE RATING	250 Vac, 32 Vdc (self certified)
TYPE	Electronic
APPLICATION	Electronic circuits

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BK/GMA-1.5-R Eaton GMA time delay glass tube fuses data sheet

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.