Specifications







Eaton SC-30

Eaton Bussmann Series Class G fuse, SC, fast-acting, current limiting fuse, 30 A, rejection style fuse, interrupting rating of 100 kA at 480 Vac and 10 kA at 300 Vdc

General specifications	
PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	SC-30
UPC	051712250306
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.62 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
PRODUCT TYPE	Fuse

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	30 A
INTERRUPT RATING	10 kAIC at 300 Vdc 100 kAIC at 480 Vac
RESPONSE TIME	12 sec at 200%
VOLTAGE RATING	480 Vac, 300 Vdc

Physical details

PACKAGING TYPE	Standard

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Ferrule design, Type P

Resources

MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - SC-30

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.