Specifications



Photo is representative

Eaton JM60030-3CHR

Eaton Bussmann series JM modular fuse block, Box Lugs with hex screws, 30 A, 3P, 120°C, 50 lb-in max, Class J, CVR(I)-J-60030, Black, 200 kAIC, 75 °C, Panel, DIN rail, 600 V, #2-14 AWG

General specifications	
PRODUCT NAME	Eaton Bussmann series JM modular fuse block
CATALOG NUMBER	JM60030-3CHR
UPC	051712620611
PRODUCT LENGTH/DEPTH	3.4 in
PRODUCT HEIGHT	2.3 in
PRODUCT WIDTH	3.3 in
PRODUCT WEIGHT	0.4334375 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	30 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	600 V

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class J
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	#2-14 AWG

General information

ACCESSORIES	CVR(I)-J-60030
CONNECTION	Box lug
MOUNTING METHOD	Panel DIN rail
SPECIAL FEATURES	Box Lugs with Hex Screws

Resources

CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf JM60030-3CHR~FUSE BLK, J 600V 30A 3P Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2201
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - JM60030-3CHR

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.