Product data sheet

Specifications



KIT FLUSH-MOUNTING POUR ATV T4

NSYPTDS4

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Drive flush mounting kit
accessory category	Mounting and fixing accessory
Product Specific Application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 PanelSeT SF and SM enclosures Altivar variable speed drive ATV340
compatibility for Altivar Process 630-930, size:	4
Motor power kW	15 kW 220/240 V 18.5 kW 220/240 V 22 kW 220/240 V 30 kW 380/480 V 37 kW 380/480 V 45 kW 380/480 V
Mounting location	1 back of enclosure mounting plate 2 inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic 1 x fan support 1 x cover for fan protection

Complementary

Permanent permissible load	63.3 lb(US) (28.7 kg)
color	Gray RAL 7035)
Height	External: 31.5 in (800 mm) Cut-out: 28.9 in (735 mm)
Width	External: 15.2 in (385 mm) Cut-out: 12.8 in (325 mm)
Depth	Wall-enclosure separation : 6.0 in (151.5 mm)
Product Weight	17.862 lb(US) (8.102 kg)
Services	Configuration of enclosure pre-drilled back Factory installation drive flush mounting kit

Environment

IP degree of protection	IP55 conforming to IEC 60529

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US1CP4E22277
Discount Schedule	CP4E
GTIN	3606485442471
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	33.071 in (84.000 cm)
Package 1 Width	16.142 in (41.000 cm)
Package 1 Length	5.118 in (13.000 cm)
Package weight(Lbs)	17.862 lb(US) (8.102 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	57.480 in (146.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	385.809 lb(US) (175.000 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	Ba0ee14c-eebb-47d8-a070-ade906247bb0
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No