# Product data sheet

Specifications



## KIT FLUSH-MOUNTING POUR ATV T5

NSYPTDS5

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range** | PanelSeT |
| **Product or Component Type** | Drive flush mounting kit |
| **accessory category** | Mounting and fixing accessory |
| **Product Specific Application** | Process and utilities |
| **Range compatibility** | Altivar variable speed drive ATV630<br>Altivar variable speed drive ATV930<br>PanelSeT SF and SM enclosures<br>Altivar variable speed drive ATV340 |
| **compatibility for Altivar Process 630-930, size:** | 5 |
| **Motor power kW** | 30 kW 220/240 V<br>37 kW 220/240 V<br>45 kW 220/240 V<br>55 kW 380/480 V<br>75 kW 380/480 V<br>90 kW 380/480 V |
| **Mounting location** | 1 back of enclosure mounting plate<br>2 inside enclosure |
| **Kit composition** | 1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts<br>1 x fixing accessories<br>1 x drilling template<br>1 x instruction sheet<br>1 x edge protector profile, plastic<br>1 x fan support<br>1 x cover for fan protection |

## Complementary

| | |
|---|---|
| **Permanent permissible load** | 129.0 lb(US) (58.5 kg) |
| **color** | Gray RAL 7035) |
| **Height** | External: 38.4 in (975 mm)<br>Cut-out: 36.2 in (920 mm) |
| **Width** | Cut-out: 15.0 in (380 mm)<br>External: 16.8 in (427 mm) |
| **Depth** | Wall-enclosure separation : 8.09 in (205.5 mm) |
| **Product Weight** | 24.440 lb(US) (11.086 kg) |
| **Services** | Configuration of enclosure pre-drilled back<br>Factory installation drive flush mounting kit |

## Environment

| | |
|---|---|
| **IP degree of protection** | IP55 conforming to IEC 60529 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

| | |
|---|---|
| **Category** | US1CP4E22277 |
| **Discount Schedule** | CP4E |
| **GTIN** | 3606485442488 |
| **Returnability** | Yes |
| **Country of origin** | FR |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 39.764 in (101.000 cm) |
| **Package 1 Width** | 17.717 in (45.000 cm) |
| **Package 1 Length** | 5.906 in (15.000 cm) |
| **Package weight(Lbs)** | 24.440 lb(US) (11.086 kg) |
| **Unit Type of Package 2** | PAM |
| **Number of Units in Package 2** | 20 |
| **Package 2 Height** | 65.354 in (166.000 cm) |
| **Package 2 Width** | 39.370 in (100.000 cm) |
| **Package 2 Length** | 47.244 in (120.000 cm) |
| **Package 2 Weight** | 518.087 lb(US) (235.000 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | Ba0ee14c-eebb-47d8-a070-ade906247bb0 |
| EU RoHS Directive | Compliant |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |