Product data sheet

Specifications



Pendant Station, 2 mechanically interlocked push buttons, NO contacts, FORWARD REVERSE, yellow enclosure, 600 VAC 5 A

9001BW93Y

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001BW
Product or Component Type	Pendant control station
Device short name	9001BW
Enclosure material	Flame-retardant PC Yellow

Complementary

Control station composition	2 push-buttons 1 NO + 1 NO, white FORWARD-REVERSE
Contacts type and composition	2 NO
Connections - terminals	Screw clamp terminals
Cable entry	0.5 inch NPT conduit entrance
Contact code designation	P600 DC-13, Ue = 600 V, Ie = 5 A B600 AC-13, Ue = 600 V, Ie = 5 A

Environment

NEMA Degree of Protection	NEMA 3R/4X
Product Certifications	CE UL CSA
Ambient Air Temperature for Operation	-13…140 °F (-25…60 °C)
Ambient Air Temperature for Storage	-40…158 °F (-40…70 °C)

Ordering and shipping details

Category	US10CS121422
Discount Schedule	0CS1
GTIN	785901852902
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	20.320 in (51.613 cm)
Package 1 Width	8.00 in (20.32 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	51.613 in (131.097 cm)
Package weight(Lbs)	11.200 oz (317.515 g)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**3 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.7 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**49**
Circularity Profile	End of Life Information
Take-back	**No**

Image of product / Alternate images

Alternative








FOR
REV