Product data sheet

Specifications



Reduced flush mounting enclosure, for TeSys GV2ME motor starter, IP55

GV2MP04

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product or Component Type	Enclosure
Device short name	GV2MP
Accessory / separate part category	Mounting accessory
Product Compatibility	GV2ME
enclosure type	Reduced flush mounting

Complementary

Auxiliary mounting location	Right
Height	5.2 in (133 mm)
Width	3.7 in (93 mm)
Depth	3.9 in (98 mm)
Product Weight	0.29 lb(US) (0.13 kg)

Environment

IP degree of protection	IP55 front face
Environmental characteristic	Standard environment
Product Certifications	UKCA CE

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0I11
GTIN	3389110446999
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.528 in (11.500 cm)
Package 1 Width	3.937 in (10.000 cm)
Package 1 Length	5.906 in (15.000 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package weight(Lbs)	7.372 oz (209.000 g)
Unit Type of Package 2	S04
Number of Units in Package 2	27
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	14.050 lb(US) (6.373 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	108
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	79.781 lb(US) (36.188 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**107 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**9 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**95 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**04104e70-ba29-493c-b2cc-b5837d1f879b**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Technical Illustration

Assembly's dimensions

