Product data sheet

Specifications



connecting cable, Harmony XBT GT, RS485 cable for Shneider Electric PLC M200/M221/M241/ M251/M340, HMI Sub-D9 to PLC RJ45

XBTZ9008

Discontinued

Discontinued on: Sep 15, 2023

End-of-service on: Dec 31, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Harmony XBT
Accessory / separate part category	Connection accessories
Accessory / Separate Part Type	Connecting cable
Product or Component Type	Connecting cable
Accessory / separate part designation	Modbus serial link
Accessory / separate part destination	XBT terminal
Cable length	8.2 ft (2.5 m)

Complementary

Product Compatibility	XBTGT2... XBTGK....
Range Compatibility	Altivar 61 TeSys U Altistart 48 Modicon M340 Lexium 05 Altivar 71 TeSys T Altivar 31 Preventa XPSMC
Electrical connection	1 male connector RJ45
Communication Port Protocol	Modbus
Physical interface	RS485

Ordering and shipping details

Category	US10MC222570
Discount Schedule	0MC2
GTIN	3595863961706
Returnability	No

Packing Units

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.79 in (2.000 cm)
Package 1 Width	5.91 in (15.000 cm)
Package 1 Length	5.91 in (15.000 cm)
Package weight(Lbs)	4.268 oz (121.000 g)
Unit Type of Package 2	S04
Number of Units in Package 2	60
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	18.342 lb(US) (8.320 kg)

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

F-gas usage performance	Only air and vacuum used for insulation / breaking, no F-gas including SF6
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	69107a2b-eec5-4280-8fc1-e988a903c9a2
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.