Product data sheet
Characteristics

ABL7RP1205
regulated SMPS, 1 or 2-phase, 100.240 V AC- 12 V, 5 A



Main

Range of product	Modicon Power Supply
Product or component type	Power supply
Power supply type	Regulated switch mode
Nominal input voltage	100...240 V AC phase to phase L1-L2 100...240 V AC single phase N-L1 110...220 V DC
Input voltage limits	100...250 V AC 85...264 V AC
Kw Rating	60 W
Output voltage	12 V DC
Power supply output current	5 A

Complementary

Input protection type	Integrated fuse (not interchangeable)
Inrush current	30 A
[Ue] rated operational voltage	12 V DC 0.98
Efficiency	85 %
Output voltage adjustment	100...120 % adjustable
Power dissipation in W	10.6 W
Current consumption	0.4 A 240 V 0.8 A 100 V
Output protection type	Against overload 1.1 x In Against overvoltage tripping if U > 1.5 x Un Against short-circuits manual or automatic reset Against undervoltage tripping if U < 0.8 x Un
Connections - terminals	Input connection screw type terminals 2 x 0.14...2 x 2.5 mm² AWG 26...AWG 14 Input ground connection screw type terminals 1 x 0.14...1 x 2.5 mm² AWG 26...AWG 14 Output connection screw type terminals 2 x 0.14...2 x 2.5 mm² AWG 26...AWG 14 Output ground connection screw type terminals 1 x 0.14...1 x 2.5 mm² AWG 26...AWG 14
Status LED	Output voltage 1 LED Green) Input voltage 1 LED Orange)
Maximum Depth	4.72 in (120 mm)
Maximum Height	4.72 in (120 mm)
Maximum Width	2.13 in (54 mm)
Net Weight	2.20 lb(US) (1 kg)
Output coupling	Parallel Series
Marking	CE
Mounting support	75 x 7.5 mm symmetrical DIN rail 35 x 15 mm symmetrical DIN rail 35 x 7.5 mm symmetrical DIN rail
Operating position	Vertical

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	CSA C22.2 No 60950-1 UL 508
Product certifications	CSA 22-2 No 950 EAC CULus 508 RCM KC TÜV
Environmental characteristic	EMC EN 50081-1 EMC EN 50082-2 EMC EN/IEC 61000-6-2 Safety EN/IEC 60950 Safety IEC 61496-1-2 Safety SELV
Operating altitude	6561.68 ft (2000 m)
IP degree of protection	IP20 EN/IEC 60529
Ambient air temperature for operation	32…122 °F (0…50 °C) without) 122…140 °F (50…60 °C) with derating factor)
Ambient air temperature for storage	-13…158 °F (-25…70 °C)
Relative humidity	0…95 % without condensation or dripping water
Dielectric strength	3000 V between input and ground 3000 V between input and output 500 V between output and ground 500 V between outputs

Ordering and shipping details

Category	22525 - ABL8 AND ABL7 POWER SUPPLIE
Discount Schedule	CP12
GTIN	00785901425267
Nbr. of units in pkg.	1
Package weight(Lbs)	2.37 lb(US) (1.08 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.56 in (6.5 cm)
Package 1 width	5.24 in (13.3 cm)
Package 1 Length	5.71 in (14.5 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	14
Package 2 Weight	34.47 lb(US) (15.634 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes


Contractual warranty

Warranty	18 months

Regulated Switch Mode Power Supply


Dimensions and Mounting

Mounting on 35 mm/1.37 in. or 75 mm/2.95 in. Rail



Regulated Switch Mode Power Supply

Internal Wiring Diagram




(1) Filter

Regulated Switch Mode Power Supplies


Series or Parallel Connection

Series Connection



(1) Two Shottky diodes Imin = power supply In and Vmin = 50 V

Parallel Connection



Family	Series	Parallel
ABL 8REM/7RP	2 products max.	2 products max.

NOTE: Series or parallel connection is only recommended for products with identical references.


Regulated Switch Mode Power Supplies

Derating

The ambient temperature is a determining factor that limits the power an electronic power supply can deliver continuously. If the temperature around the electronic components is too high, their life will be significantly reduced.

The nominal ambient temperature for the Optimum range of Phaseo power supplies is 50 °C. Above this temperature, derating is necessary up to a maximum temperature of 60 °C.

The graph below shows the power as a percentage of the nominal power that the power supply can deliver continuously, depending on the ambient temperature.



X Maximum operating temperature (°C)
(1) ABL 8REM, ABL 7RP mounted vertically

Derating should be considered in extreme operating conditions:

- Intensive operation (output current permanently close to the nominal current, combined with a high ambient temperature)
- Output voltage set above 24 Vdc (to compensate for line voltage drops, for example)
- Parallel connection to increase the total power

Regulated Switch Mode Power Supply

Temporary Overloads

