Product data sheet
Characteristics

170XTS02000
Modbus Plus RS485 T-junction - 1 female connector SUB-D 9 - 2 RJ45



Main

Accessory / separate part designation	Modbus Plus RS485 cable connector T for RJ45
Accessory / separate part type	T connector
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Modbus Plus RJ45 cable
Range compatibility	Modicon Premium automation platform Modicon Momentum automation platform Modicon Quantum automation platform Magelis XBT
Quantity per set	Set of 1

Complementary

Communication port protocol	Modbus Plus
Electrical connection	1 female connector SUB-D 9 tap link devices) 2 connectors RJ45

Environment

IP degree of protection	IP20

Ordering and shipping details

Category	18206 - MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	00785901401940
Nbr. of units in pkg.	1
Package weight(Lbs)	0.11 lb(US) (0.05 kg)
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.91 in (2.3 cm)
Package 1 width	1.18 in (3 cm)
Package 1 Length	2.36 in (6 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months