Product data sheet

Specifications



Analog Input Module + Base, 4 In, Current, Voltage, 2 Wires, Modicon Edge I/O NTS

NTSAMI0400K

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon Edge I/O NTS
Product or Component Type	Analog input module kit
Kit composition	NTSAMI0400 module NTSXBA0100H base
Mandatory accessory	NTSXTB12_0_H terminal block
Product Compatibility	NTSN.....
Range Compatibility	Logic/motion controller - Modicon M262 Modicon M580 Third party
Device Application	Industrial Application
Analogue input number	4
Operating Mode	Isochronous/Asynchronous

Complementary

Analogue input type	Current +/- 20 mA Current 0...20 mA Current 4...20 mA Voltage +/- 10 V Voltage 0...10 V Voltage +/- 5 V Voltage 0...5 V Voltage 1...5 V
Input wiring mode	2 wires
Analogue input resolution	15 bits + sign
Permitted overload on inputs	30 V maximum voltage 30 V at 50 mA maximum current
Input impedance	> 10 MOhm in voltage mode 100 Ohm + internal current protector 10 Ohm typical
Sampling duration	0.980 ms per module
Input protection type	Over current / miswiring protection per channel for current input Over voltage / miswiring protection per channel for voltage input
Input diagnostic	Underflow error per channel Overflow error per channel Broken wire error per channel Hardware error per channel
LSB value	0.31 mV, +/- 10 V 0.31 mV, 0...10 V 0.16 mV, +/- 5 V 0.16 mV, 0...5 V 0.13 mV, 1...5 V 0.61 µA, +/- 20 mA 0.61 µA, 0...2 mA 0.49 µA, 4...20 mA

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Type of Cable	Shielded cable
Temperature drift	± 0.0057 % FS/ °C
Measurement error	<= 0.3 % FS 25 °C <= 0.5 % FS - 20…60 °C
Non-linearity	<= 0.01 % FS voltage/current
Common mode rejection	90 dB
Power supply type	Bus power from power supply bus (24 Vdc) Field power from power supply field (24 Vdc)
Rated operational voltage limits	20.4...28.8 V DC
Typical current consumption	31.7 mA 24 V DC on the Bus current 19.2 mA 24 V DC on the internal field current minimum 23 mA 24 V DC on the internal field current maximum
Power dissipation in W	1.6 W maximum at 24 V DC
Maximum cable distance between devices	Shielded cable <656.2 ft (200 m) voltage inputs Shielded cable <3280.8 ft (1000 m) current input
Isolation between channels and bus	1500 V AC
Isolation between channels and field pwr	No
Isolation between field power and bus	1500 V AC
Hot swapping fallback	Yes
Local signalling	1 LED green module operating (RUN) 1 LED per channel green channel diagnostic 1 LED red module error (ERR)
Housing Colour	Grey
Mounting support	Top hat type TH35-7.5 rail IEC 60715 Top hat type TH35-15 rail IEC 60715
Height	3.9 in (100 mm)
Width	0.6 in (15 mm)
Depth	3.1 in (80 mm)
Product Weight	0.161 lb(US) (0.073 kg)

Environment

IP Degree of Protection	IP20
Marking	CE UKCA CULus RCM
Product certifications	CE UKCA CULus RCM Merchant Navy - EU RO MR (pending) EAC (pending) ATEX Zone 2 (pending) IECEx zone 2 (pending) CCC Ex zone 2 (pending)

Standards	EN/IEC 61131-2 EN 61010-2-201 UL 61010-2-201 IACS E10 EN/IEC 61000-6-5 EN/IEC 61850-3 EN/IEC 60079-0 EN 50155 EN 50121-4 EN 50121-5
Directives	2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive 2014/35/EU
Ambient air temperature for operation	-4…140 °F (-20…60 °C)
Ambient air temperature for storage	-40…185 °F (-40…85 °C)
Relative humidity	5…95 % without condensation
Operating altitude	0...6561.68 ft (0...2000 m) 2000...5000 m with derating
Pollution degree	2
Vibration resistance	1 g without accessory 2 g with accessory
Shock resistance	15 g 11 ms with and without accessory)

Ordering and shipping details

Category	US1PC3318214
Discount Schedule	PC33
GTIN	3606486877357
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.181 in (3.000 cm)
Package 1 Width	3.543 in (9.000 cm)
Package 1 Length	4.724 in (12.000 cm)
Package weight(Lbs)	3.492 oz (99.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	16
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	5.906 in (15.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	4.120 lb(US) (1.869 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**24 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**6 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**18 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**66dc73d1-d186-4343-b24e-84507e018951**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**


Use Again

Repack and remanufacture

Recyclability potential, in %	**0**
Circularity Profile	**End of Life Information**
Take-back	**No**


Dimensions Drawings

Dimensions



Mounting and Clearance


Minimum clearances



a : 50 mm (1.97 in) **b :** Without EMC kit: 25 mm (0.98 in), with EMC 55 kit: 55 mm (2.16 in) **c :** 80 mm (3.15 in) **d :** 25 mm (0.98 in)

Connections and Schema


Wiring



1 : External SELV supply


Technical Illustration

Dimensions



Technical Illustration

Wiring diagram




1 : External SELV supply

Image of product / Alternate images

Alternative






AMI0400
Use NTSXTB12*0*H


PF:XX RL:XX SV:X.X.X.XXX
SN:PPYYWWDLLLNNNNN
Made in: INDONESIA

