Product data sheet

Specifications



Analog Output Module + Base, 4 Out, Current, Voltage, Modicon Edge I/O NTS

NTSAMO0400K

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon Edge I/O NTS
Product or Component Type	Analog output module kit
Kit composition	NTSAMO0400 module NTSXBA0100H base
Mandatory accessory	NTSXTB12_0_H terminal block
Product Compatibility	NTSN.....
Range Compatibility	Logic/motion controller - Modicon M262 Modicon M580 Third party
Device Application	Industrial Application
Analogue output number	4
Operating Mode	Isochronous/Asynchronous

Complementary

Analogue output type	Current 0...20 mA Current 4...20 mA Voltage +/- 10 V Voltage 0...10 V Voltage +/- 5 V Voltage 0...5 V Voltage 1...5 V
Output wiring mode	2 wires
Output protection type	16 mA short circuit and 30V over voltage for voltage output 30V over voltage for current output
Output diagnostic	Underflow error per channel Overflow error per channel Broken wire error per channel Short circuit error per channel Hardware error per channel Calibration error per channel DAC power error per channel Internal field power supply error per channel
Load impedance ohmic	600 Ohm current 1 kOhm voltage
Response time on output	912 µs at 600 Ohm per module
HART tolerance	Yes
Type of Cable	Shielded cable
Temperature drift	± 0.002 % FS/ °C
Measurement error	<= 0.1 % FS 25 °C <= 0.2 % FS - 20…60 °C
Non-linearity	<= 0.02 % FS voltage/current

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Power supply type	Bus power from power supply bus (24 Vdc) Field power from power supply field (24 Vdc)
Rated operational voltage limits	20.4...28.8 V DC
Typical current consumption	34.6 mA 24 V DC on the Bus current 24 mA 24 V DC on the internal field current minimum 79.2 mA 24 V DC on the internal field current maximum
Power dissipation in W	1.7 W maximum at 24 V DC
Maximum cable distance between devices	Shielded cable <656.2 ft (200 m) voltage inputs Shielded cable <3280.8 ft (1000 m) current input
Isolation between channels and bus	1500 V AC
Isolation between channels and field pwr	No
Isolation between field power and bus	1500 V AC
Hot swapping fallback	Yes
Local signalling	1 LED green module operating (RUN) 1 LED per channel green channel diagnostic 1 LED red module error (ERR)
Housing Colour	Grey
Mounting support	Top hat type TH35-7.5 rail IEC 60715 Top hat type TH35-15 rail IEC 60715
Height	3.9 in (100 mm)
Width	0.6 in (15 mm)
Depth	3.1 in (80 mm)
Product Weight	0.161 lb(US) (0.073 kg)

Environment

IP Degree of Protection	IP20
Marking	CE UKCA CULus RCM
Product certifications	CE UKCA CULus RCM Merchant Navy - EU RO MR (pending) EAC (pending) ATEX Zone 2 (pending) IECEx zone 2 (pending) CCC Ex zone 2 (pending)
Standards	EN/IEC 61131-2 EN 61010-2-201 UL 61010-2-201 IACS E10 EN/IEC 61000-6-5 EN/IEC 61850-3 EN/IEC 60079-0 EN 50155 EN 50121-4 EN 50121-5
Directives	2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive 2014/35/EU
Ambient air temperature for operation	-4…140 °F (-20…60 °C)
Ambient air temperature for storage	-40…185 °F (-40…85 °C)

Relative humidity	5…95 % without condensation
Operating altitude	0...6561.68 ft (0...2000 m) 2000...5000 m with derating
Pollution degree	2
Vibration resistance	1 g without accessory 2 g with accessory
Shock resistance	15 g 11 ms with and without accessory)

Ordering and shipping details

Category	US1PC3318214
Discount Schedule	PC33
GTIN	3606486877425
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.465 in (8.800 cm)
Package 1 Width	1.063 in (2.700 cm)
Package 1 Length	4.449 in (11.300 cm)
Package weight(Lbs)	3.598 oz (102.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	16
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	5.906 in (15.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	4.206 lb(US) (1.908 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**29 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**9 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**19 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.2 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**


Use Again

Repack and remanufacture

Recyclability potential, in %	**0**
Circularity Profile	End of Life Information
Take-back	**No**


Dimensions Drawings

Dimensions



Mounting and Clearance


Minimum clearances



a : 50 mm (1.97 in) **b :** Without EMC kit: 25 mm (0.98 in), with EMC 55 kit: 55 mm (2.16 in) **c :** 80 mm (3.15 in) **d :** 25 mm (0.98 in)

Connections and Schema


Wiring



1: Actuator **2**: 2-wire connection for Voltage output **3**: 2-wire connection for Current output


Technical Illustration

Dimensions



Technical Illustration


Wiring diagram



1: Actuator
2: 2-wire connection for Voltage output
3: 2-wire connection for Current output

Image of product / Alternate images

Alternative








AMO0400
Use NTSXTB12*0*H