Product data sheet

Specifications



APC Smart-UPS X-Series External Battery Pack Rack/Tower 48V, 864VAh, rackmount, 2U

SMX48RMBP2U

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Main Input Voltage	48 V DC
Product or Component Type	External battery pack
Number of rack unit	2U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide Rack Mounting brackets
Range of Product	Smart-UPS Battery Systems
Replacement battery	APCRBC115

Batteries & Runtime

Device mounting	Enclosed battery cartridge
Included Battery Modules	0
Battery Slots Empty	0
RBC Quantity	2
Battery Voltage	48V

Physical

Color	Black
Height	3.5 in (89 mm)
Width	17.008 in (432 mm)
Depth	19.3 in (490 mm)
Product Weight	63.14 lb(US) (28.64 kg)
Mounting Mode	Rack-mounted

Ordering and shipping details

Category	11309-APC RESALE PRODUCTS
Discount Schedule	APC1
GTIN	731304268611
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package 1 Height	9.843 in (25.000 cm)
Package 1 Width	23.228 in (59.000 cm)
Package 1 Length	24.409 in (62.000 cm)
Package weight(Lbs)	78.101 lb(US) (35.426 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	4
Package 2 Height	35.433 in (90.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	338.860 lb(US) (153.704 kg)
SCC14	731304268611

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**163 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**131 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**9 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**10 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**124 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**12 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**5ac12844-46eb-471b-94f1-318e06a714a6**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**48**
Circularity Profile	**End of Life Information**
Removable battery	**User replaceable**
Take-back	**Yes**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Image of product / Alternate images

Alternative






APC