ASSO | SONOMA™

WALL FAN HEATER



SONOMA™

5 YEAR WARRANTY

THE NEW STANDARD IN FAN HEATERS

The SONOMA fan heater is the new standard for those who need a quiet but fast heating solution. With the same footprint as most popular models, the SONOMA offers easy one-screw cover installation. Its impact-resistant facade makes it a safe and sustainable choice. Ideal for your bathroom, the integrated timer provides the warmth you want right when you need it most. Designed with the user experience in mind, the SONOMA fan heater provides optimal comfort to any room.

QUICK AND EASY INSTALLATION
EASILY RETROFITS MOST POPULAR MODELS

VERY QUIET FAN HEATER
CAN BE INSTALLED IN A CHILD'S BEDROOM

DESIGNED WITH THE USER EXPERIENCE IN MIND
CONTROLS LOCATED AT THE TOP OF THE UNIT

OPTIMAL SAFETY
INTEGRATED THERMAL CUTOFF
IMPACT-RESISTANT FACADE

FAST COMFORT
RAPID TEMPERATURE RISE

COLOR
- white

FINISH
- epoxy-polyester powdercoat

MANUFACTURING
- 22-gauge steel cabinet and 20-gauge steel grille
- thermal protection with automatic reset
- additional thermal protection with a thermal fuse (must be replaced if triggered)

ELEMENT
- nichrome element produces instant heat

CONTROL
- built-in thermostat (optional)
- built-in timer (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended

INSTALLATION
- recessed
- wall mounted with surface adaptor (optional)

WARRANTY
- five years

IDEAL FOR:
bedroom, living room, kitchen, hallway, lobby, office, bathroom (model with timer and thermostat)

ACCESSORIES

PRODUCT	DESCRIPTION
ASSOBB6	back box (6)
ASSOT1W	built-in single pole thermostat [120 V-347 V]
ASSOT2W	built-in double pole thermostat [120V-347V]
ASSOSAW	surface adaptor (white)

°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. **Returns are not accepted for orders of products with optional colors.**
For all the latest models and prices, please refer to our website at www.stelpro.com.

FC_ASSO_US_160718



TECHNICAL SPECIFICATIONS

WITHOUT THERMOSTAT	BUILT-IN THERMOSTAT	BUILT-IN THERMOSTAT AND TIMER	VOLTAGE	POWER	HEIGHT	LENGTH	WEIGHT
CODE	CODE	CODE	VOLTS	WATTS*	IN.	IN.	LB
ASSO1001WCW	**ASSO1001T2W**	**ASSO1001T2TW**	120	1000 or 500	12 3/8	9 1/16	7.4
ASSO1008WCW	**ASSO1008T2W**	**ASSO1008T2TW**	208	1000 or 500	12 3/8	9 1/16	7.4
ASSO1002WCW	**ASSO1002T2W**	**ASSO1002T2TW**	240/208	1000/750 or 500/375	12 3/8	9 1/16	7.4
ASSO1501WCW	**ASSO1501T2W**	**ASSO1501T2TW**	120	1500 or 750	12 3/8	9 1/16	7.4
ASSO1502WCW	**ASSO1502T2W**	**ASSO1502T2TW**	240/208	1500/1125 or 750/560	12 3/8	9 1/16	7.4
ASSO2008WCW	**ASSO2008T2W**	**ASSO2008T2TW**	208	2000 or 1000	12 3/8	9 1/16	7.4
ASSO2002WCW	**ASSO2002T2W**	**ASSO2002T2TW**	240/208	2000/1500 or 1000/750	12 3/8	9 1/16	7.4

* Choice of power at installation.

TECHNICAL DRAWINGS

