T5461-W



Tamper-Resistant Single Receptacle, 20 Amp 250 Volt, White

Single Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 250 Volt, Back and Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's 250 Volt Tamper-Resistant Receptacles are the industry's first and only solution to the revisions of the NEC Article 406.12!

- Brass self-grounding clip is permanently staked on for secure and reliable performance
- Tamper-resistant shutters
- Accommodates back and side wiring
- Face made of impact-resistant engineering polymer

Color : White

UPC Code : 078477066225

Country Of Origin : Mexico

NEMA : 

6-20R

Available Colors :

Black | Brown | Gray | Ivory | Light Almond

Technical Information

Electrical Specifications

Amperage : 20 A

Dielectric Voltage : 2000 VAC

Grounding : Self-Grounding

HP Rating : 2 HP

Pole : 2

Temperature Rise : Max 30 C

Voltage : 250 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : Maximum Continuous 75°C, minimum -40°C (w/o impact)

Material Specifications

Body Material : Nylon

Face Material : PBT

Ground Contacts : Phosphor Bronze

Grounding Screw : #8 Brass

Line Contacts : Brass Triple Wipe 0.040"

Mounting Screws : #6 Plated Steel

Mounting Strap : Galvanized Steel

Tamper Resistant Shutter Mechanism : Thermoplastic

Terminal Clamps : Galvanized Steel

Terminal Screws : #10 Brass

Mechanical Specifications

Product ID : Ratings are Marked on Device

Strap Construction :

Terminal Accom. : #14-#10 AWG Solid or Stranded

Termination : Back & Side Wire

Product Features

Color : White

Device Type : Single Receptacle Outlet

Feature : Tamper-Resistant , Smooth Face , RoHS Compliant

Grade : Heavy-Duty Industrial Specification Grade

NEMA : 6-20R

Standards & Certifications

NEMA Rating : WD-1 and WD-6

Standards and Certifications : UL 498; CSA C22.2, No. 42; Fed Spec WC-596; NOM

Warranty

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:		CATALOG NUMBERS:	
JOB NUMBER:			

Leviton Manufacturing Co., Inc.
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx



Visit our Website at: www.leviton.com
© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/