515AN

15 Amp, 125 Volt, NEMA 5-15P, 2-Pole, 3-Wire Grounding Angle Plug, Straight Blade, Commercial Grade - White



UPC Code : 078477842942

Country Of Origin : Mexico

NEMA :  5-15P

Technical Information

Electrical Specifications

Amperage : 15 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40°C to 60°C

Material Specifications

Assembly Screws : Steel, Zinc Plated

Blades/Contacts : Brass

Body Material : PVC

Color : White

Mechanical Specifications

Cord Range : .245 - .700

Product ID : Ratings and NEMA I.D. permanently marked on device

Terminal Accom. : 18-12 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Color : White

NEMA : 5-15P

Standards and Certifications

ANSI : C-73


CSA C22.2 No. 42 : File LR-406

NEMA : WD-6

NOM : 057

UL498 : File E13393

Warranty : 2-Year Limited



5-15P

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx



Visit our Website at: www.leviton.com
© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/