

TC-Rated 5" and 6" 2000 Lumen LED Downlights

High performance, energy efficient fixtures for high ceiling applications





Delivering over 2000 lumens of brilliant LED illumination, Juno TC20LED and TC22LED 2000 Lumen Series LED downlights deliver ultra-efficient, high-performance illumination for even the highest ceilings. For use in non-insulated applications, these fixtures provide 11 or more years of maintenance-free, replacement-free service when operated on a 12-hour per day basis.

Features include:

- Dedicated, TC-rated 5" or 6" new construction housings
- Ultra-efficient 26-watt operation, provides 55% energy savings compared to two 26-watt CFLs
- Deeply regressed LED diffusing lens produces even aperture luminance and low glare
- Wide flood optic (standard); medium flood, narrow flood, or spot optics are optional
- Superior fixture-to-fixture color uniformity
- 90+ CRI ensures outstanding color rendering
- High-purity aluminum housing provides uninterrupted heat transfer
- 50,000-hour service life

ENERGY STAR

JUNO®

Juno® TC-Rated 5" and 6" 2000 Lumen LED Downlights

Supplying over 2000 lumens of high-quality white light from just 26-watts, Juno TC20LED and TC22LED 2000 Lumen LED Downlights are ideal for the higher ceilings typical of retail and commercial environments. These dedicated new construction housings include an integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Open, lensed, wall wash, and ultra-low-glare hyperbolic trims are available in a variety of colors and finishes. Options include emergency battery back-up and a Chicago Plenum version. The fixtures are ENERGY STAR® certified when used with select trims.

Ordering Information

5" TC 2000 Lumen Series Generation 4 LED Downlights

Example: TC20LED G4 20LM 27K 90CRI MVOLT EZ1 BR

Series	Gen	Lumens	CCT	CRI	Voltage/Driver	Options
TC20LED 5" New Construction Housing	**G4**	**20LM** 2000 Lumens	**27K** 2700K **30K** 3000K **35K** 3500K **40K** 4000K	**90CRI** 90 CRI	**MVOLT EZ1*** Multi-Volt (120-277V) eldoLED 0-10V, 1% dim **MVOLT EZ10*** Multi-Volt (120-277V) eldoLED 0-10V, 10% dim **MVOLT ECOS3†** Lutron® Hi-Lume® Dimmable Driver	**BR** Emergency Battery Back-Up with Remote Switch **CP †** Chicago Plenum


5" Universal Voltage


5" Emergency Backup with Remote Switch


5" Chicago Plenum

*A+ Capable † Not available with emergency option.

6" TC 2000 Lumen Series Generation 4 LED Downlights

Example: TC22LED G4 20LM 27K 90CRI MVOLT EZ1 BR

Series	Gen	Lumens	CCT	CRI	Voltage/Driver	Options
TC22LED 6" New Construction Housing	**G4**	**20LM** 2000 Lumens	**27K** 2700K **30K** 3000K **35K** 3500K **40K** 4000K	**90CRI** 90 CRI	**MVOLT EZ1*** Multi-Volt (120-277V) eldoLED 0-10V, 1% dim **MVOLT EZ10*** Multi-Volt (120-277V) eldoLED 0-10V, 10% dim **MVOLT ECOS3†** Lutron® Hi-Lume® Dimmable Driver	**BR** Emergency Battery Back-Up with Remote Switch **CP †** Chicago Plenum


6" Universal Voltage


6" Emergency Backup with Remote Switch


6" Chicago Plenum

*A+ Capable † Not available with emergency option.

Accessories

Catalog No.	Description
HB1	Two 13-1/2" - 25" Real Nail® 3 bar hangers
HB26	Two 26" C-channel bar hangers
HB50	Two 50" C-channel bar hangers
LB27	Two 27" linear bar hangers

LED Optics

Catalog No.	Description
LEDOPTICG3 MFL	Medium Flood Optic (50º)
LEDOPTICG3 NFL	Narrow Flood Optic (37º)
LEDOPTICG3 SP	Spot Optic (10º)

Extensive Trim Options

Juno TC-Rated LED recessed housings are compatible with a broad selection of existing Juno 5" and 6" open, lensed and hyperbolic trims. A dedicated wall wash scoop is also available for wall wash applications.


Baffle


Cone


Hyperbolic


Decorative


Wall Wash


Frosted Lens


Regressed Baffle


Dome Lens

A+ Capable configurations support A+ Certified Solutions. A+ Certified solutions from Acuity Brands help you quickly and confidently select and implement lighting systems that are both compatible and consistent. Go to www.acuitybrands.com/APlus or contact your local Acuity Brands representative for more information.

All trademarks referenced are property of their respective owners. Specifications subject to change without notice. Printed in the U.S.A.

1300 South Wolf Road | Des Plaines, IL 60018 | Phone: 847.827.9880 | www.acuitybrands.com
© 2017 Acuity Brands Lighting, Inc. All rights reserved. | JUN_5974_1017