

Photo Credit: Culvers Headquarters, Prairie du Sac, WI (Gary Bartholomew Photography)

TC-Rated 5" and 6" 900 Lumen LED Downlights

Quality, efficient LED lighting for retail and commercial spaces





Gen 4 Juno® 5" and 6" TC 900 lumen LED downlights are more efficient than ever. They feature sophisticated optics and an array of dimmable driver options. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Designed for new construction, non-insulated applications, these downlights are ideal for the higher ceilings found in many retail and commercial facilities.

Features include:

- Dedicated, TC-rated 5" or 6" new construction housings
- Ultra-efficient 18-watt operation, provides 30% energy savings compared to equivalent CFL fixtures
- Deeply regressed LED diffusing lens produces even aperture luminance and low glare
- Wide flood optic (standard); medium flood, narrow flood, or spot optics are optional
- Superior fixture-to-fixture color uniformity
- 90+ CRI ensures outstanding color rendering
- High-purity aluminum housing provides uninterrupted heat transfer
- 50,000-hour service life

ENERGY STAR

JUNO®

Juno® TC-Rated 5" and 6" 900 Lumen LED Downlights

High-performance illumination for retail and commercial environments

Generation 4, TC20LED and TC22LED 900 Lumen LED downlights produce 900 brilliant lumens from an energy-efficient 18 watts. All trims, including the new hyperbolic style, feature a variety of colors and finishes to suit any décor. Housing options include emergency battery back-up and a Chicago Plenum version. ENERGY STAR® certified when used with select open trims.

Ordering Information

5" TC 900 Lumen Generation 4 LED Downlights

Example: TC20LED G4 09LM 27K 90CRI MVOLT EZ1 BR

Series	Gen	Lumens	CCT	CRI	Voltage/Driver	Options
TC20LED 5" New Construction Housing	**G4**	**09LM** 900 Lumens	**27K** 2700K **30K** 3000K **35K** 3500K **40K** 4000K	**90CRI** 90 CRI	**MVOLT EZ1*** Multi-Volt (120-277V) eldoLED 0-10V, 1% dim **MVOLT EZ10*** Multi-Volt (120-277V) eldoLED 0-10V, 10% dim **MVOLT ECOS3**† Lutron® Hi-Lume® Dimmable Driver	**BR** Emergency Battery Back-Up with Remote Switch **CP** † Chicago Plenum


5" Universal Voltage


5" Emergency Backup with Remote Switch


5" Chicago Plenum

6" TC 900 Lumen Generation 4 LED Downlights

Example: TC22LED G4 09LM 27K 90CRI MVOLT EZ1 BR

Series	Gen	Lumens	CCT	CRI	Voltage/Driver	Options
TC22LED 6" New Construction Housing	**G4**	**09LM** 900 Lumens	**27K** 2700K **30K** 3000K **35K** 3500K **40K** 4000K	**90CRI** 90 CRI	**MVOLT EZ1*** Multi-Volt (120-277V) eldoLED 0-10V, 1% dim **MVOLT EZ10*** Multi-Volt (120-277V) eldoLED 0-10V, 10% dim **MVOLT ECOS3**† Lutron® Hi-Lume® Dimmable Driver	**BR** Emergency Battery Back-Up with Remote Switch **CP** † Chicago Plenum


6" Universal Voltage


6" Emergency Backup with Remote Switch


6" Chicago Plenum

*A+ Capable † Not available with emergency option.

Accessories

Catalog No.	Description
HB1	Two 13-1/2" - 25" Real Nail® 3 bar hangers
HB26	Two 26" C-channel bar hangers
HB50	Two 50" C-channel bar hangers
LB27	Two 27" linear bar hangers

LED Optics

Catalog No.	Description
LEDOPTICG3 MFL	Medium Flood Optic (50º)
LEDOPTICG3 NFL	Narrow Flood Optic (37º)
LEDOPTICG3 SP	Spot Optic (10º)

Extensive Trim Options

Juno TC-Rated LED recessed housings are compatible with a broad selection of existing Juno 5" and 6" open, lensed and hyperbolic trims. A dedicated wall wash scoop is also available for wall wash applications.


Baffle


Cone


Hyperbolic


Decorative


Wall Wash


Frosted Lens


Regressed Baffle


Dome Lens

A+ Capable configurations support A+ Certified Solutions. A+ Certified solutions from Acuity Brands help you quickly and confidently select and implement lighting systems that are both compatible and consistent. Go to www.acuitybrands.com/APlus or contact your local Acuity Brands representative for more information.

JUNO®

All trademarks referenced are property of their respective owners. Specifications subject to change without notice. Printed in the U.S.A.

1300 South Wolf Road | Des Plaines, IL 60018 | Phone: 847.827.9880 | www.acuitybrands.com
© 2017 Acuity Brands Lighting, Inc. All rights reserved. | JUN_5975_1017

AcuityBrands.