ALLIED MOULDED PRODUCTS, Inc.
222 N Union Street • Bryan, OH 43506
Ph: (800) 722-2679 • Fx: (800) 237-7269
Email: sales@alliedmoulded.com
www.alliedmoulded.com

P-181H



Product Description

Single gang electrical box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: P-181H

Height: 3-3/4 in.
Width: 2-5/16 in.
Depth: 2-3/4 in.
Volume: 18 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 1

Carton Quantity: 48
Carton Weight: 10 lb.

UPC: 085339249160
UNSPSC: 39121308
Country of Origin: United States of America

FEATURES

Molded-in splined device holes, leveling ribs

APPLICATION

New work residential construction 2 HR fire resistive walls & ceilings

STANDARDS

ANSI / UL 514C: File No. E30594

FIRE CLASSIFICATION

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less
Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less
Distance between boxes must be 4-½ feet from one another
Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

MATERIAL

Polyvinyl Chloride

MOUNTING

Stud face mount molded-in hanger bracket with 1/2" offset and opposite side drywall tabs

ADDITIONAL MATERIALS

Galvanized snap in bracket

© 2018 Allied Moulded Products, Inc.