BURNDY

BG24N Flexible Copper Braid, 24 in L, .25 IN Thickness

By Burndy
Catalog # BG24N

Flexible Copper Braid, 24 in L, .25 IN Thickness



Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool: www.hubbell.com/config/BRAID

Application

Flexible copper braid jumpers designed to take up linear expansion and contraction

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Configuration

Connector Type	Braid

Current

Rating - Indoor Amperage	415
Rating - Outdoor Amperage	495

Dimensions

Dimension - L Length Overall mm	610 mm
Dimension - Pad Width inch	1.50 in
Dimension - Hole Size inch	0.56 in
Length	24 in
Dimension - Length Overall inch	24.00 in
Dimension - D inch	3.00 in
Height	0.25 in
Dimension - N inch	0.62 in

General

Material - Ferrules	Y
Sub Brand	BRAID
Physical Attribute - Number of Braids	1
Plated	N
Type	B, Flexible
UPC 12 Digit	781810005262
UPC 14 Digit GTIN	00781810005262
Material	Copper
UPC	781810005262

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	276

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved