
YGIBS283382N Structural Steel Compression Grounding Connector



By Burndy
Catalog # YGIBS283382N

Copper Compression Connector, Cable to Steel, 2 AWG - 4/0 AWG, Angled Flange, 0.25" - 0.338" Thickness, 2 holes, 1/2" Stud

Features

- Irreversible compression ground connector allowing attachment to a structural steel standard (Angled) or wide flange (Parallel) beam
- Made of high conductivity wrought copper and prefilled with PENETROX™ E compound and strip sealed

Application

For Direct Burial Cables

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Size Range	2 AWG-4/0 AWG
Conductor Type	CU C Str-Size

Configuration

Connector Type	Tap

Dimensions

Dimension - L Length Overall mm	76 mm
Dimension - Height fraction	1-10/77 in
Dimension - Height inch	1.13 in
Dimension - Height mm	28.7 mm
Dimension - I Beam Thickness inch	0.250" - 0.338"
Dimension - B Length fraction	3 in
Dimension - B Length inch	3.00 in
Dimension - I Beam Thickness Range inch	0.250;0.275;0.300;0.312
Dimension - Length Overall inch	3.00 in

General

Trade Name	GROUNDLINK™
Sub Brand	HYGROUND, GROUNDLINK
Plated	N
Type	Taps
UPC 12 Digit	781810039281
UPC 14 Digit GTIN	00781810039281
Material	Copper
Plating Type	Unplated
I Beam Style	Standard Beam (Flange Angled)
UPC	781810039281

Logistics

Minimum Pack Quantity	1
Carton Quantity	6
Pallet Quantity	1782

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved