CFDFR, Black Cover, Flame retardant cover for YH2929, 250 kcmil H-Tap



By Burndy
Catalog # CFDFR

Black Cover, Flame retardant cover for YH2929, 250 kcmil H-Tap

Features

- Connector end stops
- Flexible fingers
- snap tight latches
- Hinged one piece contruction

Application

Cover

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
Certification - 94V0 Rated	N
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Conductor - Max Length	0.95 in
Wire Size	250 KCMIL
Conductor - Copper Str Size	250 KCMIL
Conductor - AL Str Size	250 KCMIL
Conductor - Copper Str Compact Size	250 KCMIL
Conductor - Copper Str Size Range	250 kcmil
Conductor Type	CODE/FLEX

Configuration

Connector Type	H-TAP COVERS BLACK

Current

Voltage - Maximum	35000
Voltage Rating	600 V

Dimensions

Dimension - L Length Overall mm	86 mm
Dimension - Height inch	2.02 in
Dimension - Width inch	1.59 in
Thickness	0.08 in
Dimension - Length Overall inch	3.39 in
Dimension - Maximum Conductor Size Accommodated	250 kcmil

General

Trade Name	CRIMPIT™
Insulation	Y
Sub Brand	CRIMPIT
Color Code	Purple
Color	Black
Plated	N
Type	CF-FR, Flame Retardant
Fire Resistance	Yes
UPC 12 Digit	781810132395
UPC 14 Digit GTIN	00781810132395
Material	POLYCARBONATE
Plating Type	Unplated
UPC	781810132395

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	3600

Operational

Operating Temperature	90 °C
Temperature Rating	194

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved