BURNDY

YGHR26C58 Figure 8 Compression Ground Rod Connector



By Burndy
Catalog # YGHR26C58

HYTAIL™ Ground Rod Figure 8 Compression Tap Connector

Features

- High torque strength ground rod connector accepts a wide range of copper conductors to ground rod
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	• UL467 • IEEE 837
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	• UL467 • IEEE 837
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rod Size	5/8 in
Conductor - Copper Str Size	• 2 AWG • 1 AWG • 1/0 • 2/0 AWG
Conductor - Rod Size Range	5/8 in
Conductor - Copper Str Size Range	2 AWG - 2/0 AWG
Conductor Type	• CU C Str-Size A • Rod-Size B

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - L Length Overall mm	22 mm
Dimension - Ground Rod Size	5/8
Dimension - Height fraction	1-32/33 in
Dimension - Height inch	1.97 in
Dimension - Height mm	50 mm
Dimension - B Length fraction	22/25 in
Dimension - B Length inch	0.88 in
Dimension - Length Overall inch	0.88 in

General

Die Index	• 998 • 1012
Trade Name	HYTAIL™
Precrimp Die	UPRECRIMP58
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox E
Sub Brand	HYGROUND, HYTAIL
Plated	N
Type	Taps
UPC 12 Digit	781810220719
UPC 14 Digit GTIN	00781810220719
Material	Copper
Plating Type	Unplated
UPC	781810220719

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	4640

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved