GSTUD34HY Structural Steel Ground Stud



By Burndy
Catalog # GSTUD34HY

Structural Steel Grounding Connector

Features

- May be welded to steel surfaces quickly and easily
- No disk grinding needed
- Knurled surface for better gripping
- Copper plated
- May be installed during adverse weather conditions

Application

For Compression Connectors And Mechanical Connectors

Specifications

Certification - UL Recognized	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - UL Listed Direct Burial	No
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Rod Size Range	3/4 in
Conductor - Copper Str Size	4/0 AWG
Conductor - Rod Size	3/4 in
Conductor Type	• Rod-Size • CU C Str-Size
Conductor - Copper Str Size Range	4/0 AWG

Dimensions

Dimension - Ground Rod Size	3/4 in
Package Height	0.000 in
Dimension - Height mm	0 mm
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	148 mm
Physical Attribute - Tongue Angle	45 Degree
Dimension - B Length fraction	19/25 in
Dimension - B Length inch	0.76 in
Dimension - D inch	1.25 in
Dimension - Length Overall inch	5.81 in

General

Trade Name	VERSITAIL™
Plated	Y
Sub Brand	HYGROUND, VERSITAIL
UPC	781810220900
Type	GSTUD-HY
Material	Steel
Plating Type	Nickel
UPC 12 Digit	781810220900
UPC 14 Digit GTIN	00781810220900

Logistics

Pallet Quantity	1960
Carton Quantity	5

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved