
# UCG25RS, Aluminum Alloy Parallel Clamp



By Burndy
Catalog # UCG25RS

Multiple purpose parallel groove clamp made of high strength, high conductivity aluminum alloy. Hardware allows for one of two wrench installation,length:1-3/8",width:1-5/8".

## Features

- Multi-purpose parallel groove clamp made of high strength, high conductivity, non-copper bearing aluminum alloy
- Properly proportioned to minimize stress corrosion and deterioration by galvanic action
- Interlocking fingers on connector body halves prevent mismatching
- Square shank, hex head, round collar, high strength galvanized steel bolt allows 1 or 2-wrench installation
- Supplied pre-filled with PENETROX™ joint compound and strip sealed

## Application

For All Combinations Of Copper, Aluminum, ACSR, 6201 And 5005

## Specifications

| | |
|---|---|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |

## Conductor

| | |
|---|---|
| Conductor - AAAC 5005 Size A Range | 30.58 (7) kcmil-123.3 (7) kcmil |
| Conductor - AAAC 5005 Size B | 30.58 (7) kcmil;48.69 (7) kcmil;77.47 (7) kcmil;123.3 (7) kcmil;155.4 (7) kcmil;195.7 (7) kcmil;246.9 (7) kcmil |
| Conductor - AAAC 5005 Size B Range | 30.58 (7) kcmil-246.9 (7) kcmil |
| Conductor - AAAC 6201 Size A | 30.58 (7) kcmil;48.69 (7) kcmil;77.47 (7) kcmil;123.3 (7) kcmil |
| Conductor - AAAC 6201 Size A Range | 30.58 (7) kcmil-123.3 (7) kcmil |
| Conductor - AAAC 6201 Size B | 30.58 (7) kcmil;48.69 (7) kcmil;77.47 (7) kcmil;123.3 (7) kcmil;155.4 (7) kcmil;195.7 (7) kcmil;246.9 (7) kcmil |
| Conductor - AAAC 6201 Size B Range | 30.58 (7) kcmil-123.3 (7) kcmil |
| Conductor - AL Str Size A | 8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG |
| Conductor - AL Str Size A Range | 8 AWG-1/0 AWG |
| Conductor - AL Str Size B | 8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG |
| Conductor - AL Str Size B Range | 8 AWG-1/0 AWG |
| Conductor - Copper Str Size A | 8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 |
| Conductor - Copper Str Size A Range | 8 AWG-1/0 |
| Conductor - Copper Str Size B | 8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 |
| Conductor - Copper Str Size B Range | 8 AWG-1/0 |
| Conductor Type | AL C Str-Size A;CU C Solid-Size A;CU C Str-Size A;AAAC C 5005-Size A;AAAC C 6201-Size A;AL C Str-Size B;CU C Solid-Size B;CU C Str-Size B;AAAC C 5005-Size B;AAAC C 6201-Size B |
| Conductor - AAAC 5005 Size A | 30.58 (7) kcmil;48.69 (7) kcmil;77.47 (7) kcmil;123.3 (7) kcmil |

## Dimensions

| | |
|---|---|
| Dimension - Height fraction | 2-1/8 in |
| Dimension - Height inch | 2.09 in |
| Dimension - Height mm | 53.1 mm |
| Dimension - Width fraction | 1-5/7 in |
| Dimension - Width inch | 1.71 in |
| Dimension - Width mm | 43 mm |
| Dimension - B Length fraction | 1-3/8 in |
| Dimension - B Length inch | 1.41 in |

## General

| | |
|---|---|
| Trade Name | TAPIT™ |
| Sub Brand | TAPIT |
| Plated | N |
| Type | UCG-RS |
| UPC 14 Digit GTIN | 00781810097809 |
| Material | Aluminum |

| | | | |
|---|---|---|---|
| Plating Type | Unplated | Carton Quantity | 100 |
| UPC | 781810097809 | Pallet Quantity | 1 |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 1 |

## Product Assets

Catalog [English]

A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved