BURNDY

GG181, Mech Ground, Cu Bar/Strap/Braid or Cable to Rod/Tube



By Burndy
Catalog # GG181

Mechanical Grounding Connector, Copper Bar/Strap/Braid/Cable to Rod/Tube, 2" Pipe, 2"-2-3/8" Rod

Features

- High copper alloy ground connector for joining bar, strap, braid or cable to rod or tube
- Rated for Direct Burial in earth or concrete
- UL467 Listed
- One wrench installation
- Type GG connector is particularly effective for use with braid for ground rods, switch handles, fence posts and gates

Application

For Joining Copper Bar, Strap, Braid Or Cable To Rod Or Tube, Direct Burial Cables

Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - UL Listed Direct Burial	Yes
UL Listed	No
Certification - CSA Approved	No

Conductor

Conductor - Copper Tube Std Size	• 2 • 2-1/4

Dimensions

Package Height	0.000 in
Dimension - Height mm	108 mm
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - Width mm	94 mm
Dimension - Width inch	3.69 in
Dimension - B Length inch	1.38 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in

General

Material Type - Screw	DURIUM™ Silicon Bronze
Plated	No
Sub Brand	MECHANICAL CONNECTOR
Product Type	Mechanical
UPC	781810260067
Type	GG
U Bolt Type	257
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC 12 Digit	781810260067
UPC 14 Digit GTIN	00781810260067

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1944
Carton Quantity	6

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved