HSC12FR, Vinyl Fire Retardant Clear Heat Shrink Tubing, #4-#1(Code) #6-#4(Flex), 600V.



By Burndy
Catalog # HSC12FR

Vinyl Fire Retardant Clear Heat Shrink Tubing, #4-#1(Code) #6-#4(Flex), 600V.

Features

- Flame Retardant
- Flexible Polyvinylchloride
- 2:1 Shrink Ratio
- 600 Volts

Application

For Terminations And Splices

General

Catalog Number	HSC12FR
Color	Clear
EU RoHS Indicator	Yes
Material	Polyvinyl chloride
Sub Brand	VISISHRINK
Trade Name	VISI-SHRINK™
Type	HSC-FR, Thin Wall, Flexible, Fire Retardant
UPC	781810266175

Conductor Related

Conductor Range	#6 AWG to #4 AWG

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	16
Minimum Pack Quantity	1

Product Assets

3D Models - HSC12FR_MODEL-PDF
3D Models - HSC12FR_MODEL-STEP
3D Models - HSC12FR_MODEL-IGES
Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide
Product Cross Section Image(s) - BUR_HSC100FR_LineArt
Sales Drawings - 50015598
Specifications - HSC12FR

©2025 Hubbell Incorporated. All rights reserved