PENEQT, Oxide Inhibitor, Quart Container

By Burndy
Catalog # PENEQT



Oxide Inhibiting Electrical Joint Compound, 1 Quart, For Cu-Cu, Cu Conduit Threads & Grounding Applications.

Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

Application

For Copper To Copper

General

Application - For Use On	Copper to Copper
Catalog Number	PENEQT
Container Type	Tub
EU RoHS Indicator	Yes
Pour Point	-40 °F
Sub Brand	PENETROX
Temperature - Dropping Point Fahrenheit	350 °F
Trade Name	PENETROX™
Type	E
UPC	781810592946
UPC 14 Digit GTIN	00781810592946
Viscosity at 100 Fahrenheit	250 °F

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	4
Container Size	1 Quart
Minimum Pack Quantity	1

Product Assets

3D Models - PENEQT_MODEL-PDF
3D Models - PENEQT_MODEL-IGES
3D Models - PENEQT_MODEL-STEP
Catalogs - BURNDY Master Catalog - Section F - Accessories
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_PENEQT_LineArt
Sales Drawings - 50016179
SDS - PENETROX E PORTUGUESE SDS
SDS - PENETROX E GERMAN SDS
SDS - PENETROX E Polish SDS
SDS - PENETROX E FRENCH SDS
SDS - PENETROX E RUSSIAN SDS
SDS - PENETROX E ESPANOL SDS
SDS - PENETROX E SDS
Specifications - PENEQT

©2025 Hubbell Incorporated. All rights reserved