Concrete Ring, Welded, 5 in. Deep, Double Row 1/2 & 3/4 in. KO's

By RACO
Catalog # 275

Concrete Ring, Welded, 5 in. Deep, Double Row 1/2 & 3/4 in. KO's



Features

- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- A variety of covers are available
- Cover plate must be orered separately with all RACO® concrete rings
- Used in high-rise construction
- 74.0 cu. in. capacity
- Not designed for ceiling fan support, the maximum support load for a static fixture is 50 lbs

Specifications

Certified Listed	UL Listed
Buy American Compliant	No
EU RoHS Indicator	Contact Manufacturer

Configuration

Knockouts	• 1/2 in • 3/4 in

Dimensions

Cubic Capacity	61.5 cu.in
Fixture Lbs.	50 lb.
Depth	5 in
Width	4 in
Weight	1.3 lb.
Height	4 in

General

Wiring System	Conduit
Color	Gray
Type	Concrete Ring
Material	Steel
Drawn or Welded	Welded
UPC	050169002759

Logistics

Packaging Type	No Packaging
Carton Quantity	10
Pallet Quantity	550

Product Assets

Catalog [English]
Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved