BURNDY

SP18BG25, Vinyl Splice For 22 - 18 AWG



By Burndy
Catalog # SP18BG25

Vinyl Splice For 22 - 18 AWG

Features

- Splices are constructed of pure electrolytic copper
- Long butted seam barrel with deep V groove inner serrations for optimum conductivity, reliability, and holding power after crimping
- Designed for joining two wire securely
- Provides maximum conductivity, low resistance, and ductility for excellent crimp forming properties
- Electro-tin plating for durable, long lasting corrosion resistance
- Inspection hole/skive provides an easy visual check of proper wire insertion
- 600 Volts Maximum, 105°C maximum

Application

For Heavy Duty Application Requirements

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
Industry Standard(s)	UL467
Certification - CSA Approved	Yes
UL Listed	Yes
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor Size	22 - 18 AWG
Conductor - Copper Str Size	20 AWG;18 AWG
Conductor - Copper Str Size Range	20 AWG-18 AWG
Conductor Type	CU C Str-Size

Configuration

Connector Type	Seamless Butt Splice

Dimensions

Package Length	3.00 in
Package Width	3.00 in
Package Weight	1.5 lb.
Package Height	4.00 in

General

Sub Brand	INSULINK
Insulation Type	Vinyl
Trade Name	VINYLINK™
Plated	Y
Feature - Barrel Style	Shrouded
Insulation	Y
Type	SN
UPC 12 Digit	781810486313
UPC 14 Digit GTIN	00781810486313
Material	Copper
Plating Type	Tin
UPC	781810486313

Logistics

Minimum Pack Quantity	5
Carton Quantity	5
Pallet Quantity	12000

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved