GCL30, Mechanical Grounding Connector, Two Cables to Bar



By Burndy
Catalog # GCL30

Cast Copper Alloy Ground Clamp, 4 Str. - 300, Cable to Bar

Features

- High copper alloy ground connector for joining a range of two parallel cables to 1/4" thick bar
- Type GC Separates cable from bar
- One-wrench installation
- UL467 Listed

Application

For Two Copper Cables To Bar And Direct Burial In Concrete Or Ground

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	4 Str;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil
Conductor - Copper Solid Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size Range	4 AWG - 300 KCMIL
Conductor - Copper Str Size Range	4 AWG - 300 kcmil

Dimensions

Dimension - L Length Overall mm	56 mm
Dimension - Height inch	2.00 in
Dimension - Height mm	50.8 mm
Dimension - Stud Size inch	33/64
Dimension - Width inch	1.50 in
Dimension - Width mm	38 mm
Dimension - Bus Thickness inch	0.25 in
Dimension - Length Overall inch	2.21 in

Force Related

Installation Torque Recommended in-lb	480 lb-in

General

Material - Hardware	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Type	GC
UPC 12 Digit	781810079478
UPC 14 Digit GTIN	00781810079478
Material	Copper Alloy
Plating Type	Unplated
UPC	781810079478

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	4536

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved