BDBLHCCOVER, Power Distribution Block Cover

By Burndy
Catalog # BDBLHCCOVER

Power Distribution Block Safety Cover



Features

- VERSIPOLE Confirgurable Power Distribution Blocks
- Available in 3 sizes for optimization of space
- Suitable for use with aluminum or copper conductors
- Single or dual run connections
- 600V Al/Cu Rated
- High short-circuit rating up to 100kA with proper fusing
- Adders and end barriers available separate for all 3 sizes

Application

Industrial control feeder, HVAC system and wire ways

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor Type	AL C Str-Run;CU C Str-Run;AL C Str-Tap;CU C Str-Tap

Current

Rating - Minimum Voltage	600

Dimensions

Dimension - Width inch	2.61 in
Dimension - Width mm	66 mm
Dimension - L Length Overall mm	154 mm
Dimension - Pad Width inch	2.61 in
Dimension - Height inch	0.87 in
Dimension - Height mm	22.1 mm
Length	5.7 in
Dimension - Length Overall inch	6.07 in
Width	4.75 in
Height	3.55 in
Dimensions	5.7 in x 4.75 in x 3.55 in

General

Sub Brand	VERSI-POLE
Trade Name	VERSIPOLE™
Plated	Y
Insulation	Y
Type	BDB
UPC 12 Digit	781810646120
UPC 14 Digit GTIN	00781810646120
Material	Aluminum
Plating Type	Tin
UPC	781810646120

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	4400

Operational

Temperature Rating	194

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved