BDCSHC142/01, 1-Pole Power Distribution Block

By Burndy
Catalog # BDCSHC142/01

Versipole, AWG 14-2/0 (Run), AWG 14-4 (Tap)



Features

- VERSIPOLE Confirgurable Power Distribution Blocks
- Available in 3 sizes for optimization of space
- Suitable for use with aluminum or copper conductors
- Single or dual run connections
- 600V Al/Cu Rated
- High short-circuit rating up to 100kA with proper fusing
- Adders and end barriers available separate for all 3 sizes

Application

VERSI-POLE Power Distribution Blocks are designed to provide modular solutions to power distribution applications.

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - AL Str Run	12;10;8;6;4;3;2;1;1/0;2/0
Conductor - AL Str Run Range	12-2/0
Conductor - AL Str Tap	12;10;8;6;4
Conductor - AL Str Tap Range	12-4
Conductor - Copper Str Run	14;12;10;9;8;7;6;5;4;3;2;1;1/0;2/0
Conductor - Copper Str Run Range	14-2/0
Conductor - Copper Str Tap	14;12;10;9;8;7;6;5;4
Conductor - Copper Str Tap Range	14-4
Conductor Type	AL C Str-Run;CU C Str-Run;AL C Str-Tap;CU C Str-Tap

Configuration

Number Of Poles	1

Current

Rating - Minimum Voltage	600
Amperage Rating	175 A

Dimensions

Dimension - L Length Overall mm	78 mm
Dimension - Height inch	2.81 in
Dimension - Height mm	71.4 mm
Width	2.25 in
Dimension - Width inch	1.05 in
Dimension - Width mm	27 mm
Length	2.91 in
Dimension - Length Overall inch	3.08 in
Height	2.81 in
Dimensions	2.91 in x 2.25 in x 2.81 in

General

Trade Name	VERSIPOLE™
Insulation	Y
Sub Brand	VERSI-POLE
Plated	N
Type	BDC
UPC 12 Digit	781810646168
UPC 14 Digit GTIN	00781810646168
Material	Aluminum
Plating Type	Unplated
UPC	781810646168

Logistics

Minimum Pack Quantity	1
Carton Quantity	36
Pallet Quantity	5940

Operational

Temperature Rating	194

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved