
KC23, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy
Catalog # KC23

Mechanical SERVIT POST™ Connector; Cable to Flat



Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

Application

For Direct Burial Applications And Used To Ground One Or Two Cables To Steel Structures, Fence Posts, Transformers, Also Used To Tap One Or Two Cables From Bus Bar

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	• 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG
Conductor - Copper Solid Size	• 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG
Conductor - Copper Solid Size Range	10 AWG-1 AWG
Conductor - Copper Str Size Range	8 AWG-2 AWG
Physical Attribute - Number of Conductors Accommodated Total	1

Dimensions

Dimension - Nut Width inch	0.81 in
Dimension - P inch	0.32 in
Dimension - Height fraction	1
Dimension - Height mm	26.7 mm
Dimension - Threads per inch	16
Dimension - B Length fraction	15/32 in
Dimension - Body Width inch	0.62 in
Dimension - Bolt Size fraction	3/8
Dimension - Length Overall inch	1.67 in
Dimension - D inch	0.63 in

Force Related

Stud Installation Torque inch pounds	280 LBS/in

General

Trade Name	SERVIT POST™
Sub Brand	SERVIT POST
Plated	N
Type	KC and K2C Series
UPC 12 Digit	781810255353
UPC 14 Digit GTIN	00781810255353
Material	Bronze, Leaded, Commercial
Plating Type	Unplated
UPC	781810255353

Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	59400

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved