Product data sheet
Characteristics

QMB325WT3
Fuse switch disconnector, QMB Fusible Panelboards, 240VAC, max 400A rating, 3 pole, single switch unit



Main

Product or Component Type	Fuse-switch disconnector
Number of poles	3
[Ue] rated operational voltage	240 V AC
Line Rated Current	400 A 240 V AC
Fuse type	T

Complementary

Number of modules	1
Standards	NEMA KS1
Height	9.02 in (229 mm)

Environment

Product Certifications	UL[RETURN]CSA

Ordering and shipping details

Category	US1PE1A00037
Discount Schedule	PE1A
GTIN	785901051053
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	35.940 lb(US) (16.302 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months