Product data sheet

Specifications



NEMA Motor Starter and contactor, Type S, isolated alarm contacts, for melting alloy overload relays, NO alarm contact

9999SO4

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Accessory
Product destination	Overload relay
Thermal overload type	Melting alloy

Complementary

Product or Component Type	Auxiliary contact
Contacts type and composition	1 NO
[Ue] rated operational voltage	600 V AC

Ordering and shipping details

Category	US10CP121761
Discount Schedule	0CP1
GTIN	785901057833
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.400 in (3.556 cm)
Package 1 Width	2.300 in (5.842 cm)
Package 1 Length	3.100 in (7.874 cm)
Package weight(Lbs)	1.760 oz (49.895 g)

Contractual warranty

Warranty (in months)	18

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant By Exemption**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Circularity Profile	**No need of specific recycling operations**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**