# Product data sheet

Specifications



## Branch unit, EZ Meter-Pak, 225A, 1 x 7 jaw socket, 208Y/120VAC, lever bypass, ringless, 1200A Al/Cu busbar

EZML331225

**Product availability: Stock - Normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product** | Meter Center Branch Unit |
| **Current Rating** | 225 A |
| **Type** | Meter-Pak |
| **Bus Rating** | 1200 A |
| **Number of Jaws** | 7 with jaw release |
| **Number of Meter Sockets** | 1 |
| **Bypass Type** | Lever bypass |
| **Socket Type** | Ringless |

## Complementary

| | |
|---|---|
| **Certifications** | UL Listed |
| **Busbar Material** | Aluminium/copper: busbar |
| **Enclosure Material** | Steel |
| **Enclosure Rating** | NEMA 3R |
| **Maximum Voltage Rating** | 208Y/120 V AC<br>240/120 V delta AC |
| **Mounting** | Surface |
| **Phase** | 3 phase in<br>3 phase out |
| **Wire Configuration** | 4-wire |
| **Height** | 39.06 in (992 mm) |
| **Width** | 19.4 in (494 mm) |
| **Depth** | 9.4 in (240 mm) |
| **Product Weight** | 106.087 lb(US) (48.120 kg) |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10DE400020 |
| **Discount Schedule** | 0DE4 |
| **GTIN** | 785901408796 |
| **Returnability** | Yes |
| **Country of origin** | MX |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 11.000 in (27.940 cm) |
| **Package 1 Width** | 21.800 in (55.372 cm) |
| **Package 1 Length** | 39.800 in (101.092 cm) |
| **Package weight(Lbs)** | 116.0007 lb(US) (52.617 kg) |
| **Unit Type of Package 2** | PAL |
| **Number of Units in Package 2** | 6 |
| **Package 2 Height** | 40.000 in (101.600 cm) |
| **Package 2 Width** | 40.000 in (101.600 cm) |
| **Package 2 Length** | 48.000 in (121.920 cm) |
| **Package 2 Weight** | 696.000 lb(US) (315.700 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **738 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **221 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **7 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0.1 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **505 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **5 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |
| PVC free | **No** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **88** |
| Circularity Profile | **No need of specific recycling operations** |
| Take-back | **No** |