Product data sheet
Characteristics

9998XD67
NEMA Control Relay, Type X, replacement relay coil, 230/250VDC

Main

Range of Product	8501X
Relay Type	Control relay
Product or Component Type	Coil

Complementary

[Uc] control circuit voltage	230/250 V DC
Coil Voltage Limits	Operational 0.8...1.1 Uc DC
Inrush Power in Watts	50 W
Sealed Power in Watts	50 W
Electrical Connection	Screw clamp terminals
Wire Gauge	AWG 18...AWG 12 copper
Terminal Tightening Torque	Control circuit 9.03…12.04 lbf.in (1.02…1.36 N.m) screw terminals
Height	2 in (50.80 mm)
Width	2.22 in (56.39 mm)
Depth	3 in (76.20 mm)

Ordering and shipping details

Category	21756-9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	785901548928
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	2.00 in (5.08 cm)
Package 1 Length	2.50 in (6.35 cm)
Package 1 Weight	0.85 oz (24.04 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months