Product data sheet

Specifications



Complete control station, Harmony 9001K, 10A, zinc, grey, 3 push buttons 3NO + 3NC OPEN CLOSE STOP, NEMA 3 4 13

9001KYK33

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001K
Product or Component Type	Complete control station
Device short name	KY 9001KY
Provided equipment	Contact block Legend plate
Contact block name	KA1

Complementary

Enclosure/cubicle description	Surface mounting
AC control voltage 50 HZ	125…600 V
Enclosure material	Die cast zinc alloy Gray
Type of Installation	Indoor/outdoor
Control station composition	3 push-buttons 3 NO + 3 NC OPEN-CLOSE-STOP
AC control voltage 60 HZ	125…600 V
DC control voltage	125…600 V
Connections - terminals	Screw-clamp terminals
[Ie] rated operational current AC	10 A
Number of command positions	3
Number of indicator lights	0
Number of push buttons	3
Number of selector switches	0
Number of key switches	0
Number of mushroom-shaped push-buttons	0
Emergency Power Off (EPO)	No
Number of contacts as normally closed contact	3
Number of contacts as normally open contact	3
Number of contacts as change-over contact	0
Housing material	Metal
Housing Colour	Grey
colour of cover	Grey

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

NEMA Degree of Protection	NEMA 4/13
IP Degree of Protection	IP66

Ordering and shipping details

Category	US10CS121426
Discount Schedule	0CS1
GTIN	785901616221
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.800 in (12.192 cm)
Package 1 Width	5.300 in (13.462 cm)
Package 1 Length	11.600 in (29.464 cm)
Package weight(Lbs)	4.449 lb(US) (2.018 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**16 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**13 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.3 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.4 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**15**
Circularity Profile	**End of Life Information**
Take-back	**No**

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

