Product data sheet

Specifications



Circuit breaker enclosure, PowerPacT P, 600A to 1200A, 2 and 3 pole, NEMA 3R, steel

P1200R

Product availability: Stock - Normally stocked in distribution facility

Main

Circuit Breaker Type	PJL PGL PKL PLL
Breaker Compatibility	Circuit breaker P 3P Circuit breaker P 2P

Complementary

Rated Current	600…1200 A
Poles Description	3P 2P
Enclosure Material	Steel
Height	52.13 in (1323.98 mm)
Width	21.0 in (533.4 mm)
Depth	9.75 in (247.65 mm)
Product Weight	117.99 lb(US) (53.52 kg)

Environment

Product Certifications	UL CSA

Environmental

NEMA Degree of Protection	NEMA 3R

Ordering and shipping details

Category	US10DE100030
Discount Schedule	0DE1
GTIN	785901474937
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.200 in (33.528 cm)
Package 1 Width	22.200 in (56.388 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	56.300 in (143.002 cm)
Package weight(Lbs)	118.0003 lb(US) (53.524 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Height	40.000 in (101.600 cm)
Package 2 Width	42.000 in (106.680 cm)
Package 2 Length	60.000 in (152.400 cm)
Package 2 Weight	708.000 lb(US) (321.143 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**405 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**313 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**15 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**77 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**7123f656-319e-4ae7-888d-d29a63a4aa90**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
Halogen content performance	**Halogen free plastic parts product**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.