Brighten



ENERGY STAR® certified LED replacement lamps

LEARN MORE AT energystar.gov

current
powered by GE



PERFORMANCE DATA

ENERGY STAR® certified LED lamps

Decorative Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Candles																	
			21250	LED4DCAM-C3/827	120	6	4.2	300		2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip
			69111	LED4DCAM-C3/850	120	6	4.2	300		5000	80	40W	15,000	Yes	★	Damp	Clear, Bent tip
		4.2	92389	LED4DCAM-W3/827	120	6	4.2	300		2700	80	40W	15,000	Yes	★	Damp	White, Bent tip
		7	21251	LED7DCAM-C3/827	120	6	4.8	500		2700	80	60W	15,000	Yes	★	Damp	Clear, Bent tip
			21231	LED4DCAC-C3/827	120	6	4.3	300		2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip
			69109	LED4DCAC-C3/850	120	6	4.3	300		5000	80	40W	15,000	Yes	★	Damp	Clear, Bent tip
		4.2	97230	LED4DCAC-W3/OTB	120	4	4.3	300		2700	80	40W	15,000	Yes	★	Damp	White, Bent tip
		7	21233	LED7DCAC-C3/827	120	6	4.8	500		2700	80	60W	15,000	Yes	★	Damp	Clear, Bent tip
Globes																	
G25	MED	4.5	39935	LED4DG25-C3-OT	120	3	4.3	290		2700	82	25W	15,000	Yes	★	Damp	Clear
			21253	LED5DG25-W3/827	120	6	4.3	350		2700	80	40W	15,000	Yes	★	Damp	White
		7	21255	LED7DG25-W3/827	120	6	4.3	500		2700	80	60W	15,000	Yes	★	Damp	White

LED Bright Stik™

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
LED Bright Stik™																	
	Med	5.5	66256	LED5.5LS3/827	120	48	4.45	450		2700	80	40W	15,000	-	★	Damp	Case = 16 3-pack
			75177	LED5.5LS3/850	120	48	4.45	450		5000	80	40W	15,000	-	★	Damp	Case = 16 3-pack
		9	75184	LED9LS3/827	120	48	4.45	800		2700	80	60W	15,000	-	★	Damp	Case = 16 3-pack
			75588	LED9LS3/850	120	48	4.45	800		5000	80	60W	15,000	-	★	Damp	Case = 16 3-pack
		12	75590	LED12LS2/827	120	32	5.24	1100		2700	80	75W	15,000	-	★	Damp	Case = 16 2-pack
			75591	LED12LS2/850	120	32	5.24	1100		5000	80	75W	15,000	-	★	Damp	Case = 16 2-pack
		15	75593	LED15LS2/827	120	32	5.24	1600		2700	80	100W	15,000	-	★	Damp	Case = 16 2-pack
			75644	LED15LS2/850	120	32	5.24	1600		5000	80	100W	15,000	-	★	Damp	Case = 16 2-pack

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

PERFORMANCE DATA ENERGY STAR® certified LED lamps

A-Line Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
A-19																	
	MED	6	69115	LED6DA19/827	120	6	4.4	480		2700	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
			69118	LED6DA19/830	120	6	4.4	480		3000	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
			69132	LED6DA19/840	120	6	4.4	480		4000	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
			69144	LED6DA19/850	120	6	4.4	480		5000	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
		10	69117	LED10DA19/827	120	6	4.4	800		2700	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			69119	LED10DA19/830	120	6	4.4	800		3000	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			69133	LED10DA19/840	120	6	4.4	800		4000	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			69146	LED10DA19/850	120	6	4.4	800		5000	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
A-21																	
	MED	12	76037	LED12DA21/827	120	6	5.16	1100		2700	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76041	LED12DA21/830	120	6	5.16	1100		3000	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76045	LED12DA21/840	120	6	5.16	1100		4000	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76102	LED12DA21/850	120	6	5.16	1100		5000	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
		15	76038	LED15DA21/827	120	6	5.16	1600		2700	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76043	LED15DA21/830	120	6	5.16	1600		3000	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76060	LED15DA21/840	120	6	5.16	1600		4000	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76117	LED15DA21/850	120	6	5.16	1600		5000	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
	MED	16	73376	LED16A30/100/827	120	6	5.31	360/1400/900		2700	80	30/70/100	25,000	-	★	Damp	White, 3-Way
			92118	LED16A30/100/5KB	120	3	5.31	360/1400/900		5000	80	30/70/100	25,000	-	★	Damp	White, 3-Way

Directional Lamps (MR16 - GU10)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
12 Volt AC/DC MR16																	
MR16	GU5.3	6.5	75155	LED6.5DMR16W82715	12	6	1.87	500	4900	2700	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White
			75153	LED6.5DMR16W83015	12	6	1.87	520	4900	3000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White
			75158	LED6.5DMR16W84015	12	6	1.87	550	5000	4000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White
			93226	LED6.5DMR16W82725	12	6	1.79	500	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White
			93222	LED6.5DMR16W83025	12	6	1.79	520	2350	3000	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White
			93228	LED6.5DMR16W84025	12	6	1.79	550	2400	4000	82	50W	25,000	Yes	★	Damp	Narrow 25° beam, White
			93227	LED6.5DMR16W82735	12	6	1.79	500	1350	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
			93223	LED6.5DMR16W83035	12	6	1.79	520	1350	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
			93229	LED6.5XDMR16W84035	12	6	1.79	550	1400	4000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
Value 12 Volt AC/DC MR16																	
	GU5.3	5.5	35542	LED5.5DMR1684035	12	6	1.86	460	1100	4000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
			35535	LED5.5DMR1683035	12	6	1.86	420	1000	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
			35540	LED5.5DMR1682735	12	6	1.86	400	1000	2700	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
		6	20165	LED6DMR16-32725	12	6	1.86	500	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White
			20168	LED6DMR16-32735	12	6	1.86	500	1350	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
			20156	LED6DMR16-38325	12	6	1.86	500	2350	3000	81	50W	25,000	Yes	★	Damp	Narrow 25° beam, White
			20157	LED6DMR16-38335	12	6	1.86	500	1350	3000	81	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
120 Volt GU10																	
MR16	GU10	3.5	37114	LED4D/GU1083035	120	6	2.1	300	550	3000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White
		4	89020	LED4D/GU10/NFLTP	120	3	2.1	250	720	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
		6	26346	LED6D/GU10/NFL/TP	120	3	2.1	430	1100	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
			37117	LED6D/GU1083035	120	6	2.1	430	1100	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

PERFORMANCE DATA

ENERGY STAR® certified LED lamps

RS Cans

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
RS Cans																	
	E26	10	95853	LED10RS4/827E26P	120	12	4.32	700		2700	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
			95854	LED10RS4/830E26P	120	12	4.32	700		3000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
			35365	LED10RS4/840E26P	120	12	4.32	700		4000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
		8	19888	LED8DRS6/827	120	4	4.96	700		2700	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
			19908	LED8DRS6/830	120	4	4.96	700		3000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
			20026	LED8DRS6/840	120	4	4.96	700		4000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
		13	20037	LED13DRS6/827	120	4	4.96	1000		2700	80	90W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
			20048	LED13DRS6/830	120	4	4.96	1000		3000	80	90W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment

Directional Lamps (PAR38 - Value)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Single Optics 15W PAR38																	
	MED	15	32213	LED15DP38W830/40	120	6	5.04	1300	2300	3000	81	90W	25,000	Yes	★	Wet	Flood, 40° beam, White, STIR

Directional Lamps (PAR)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
PAR38 - Low Glare - Visual Comfort Lens™																	
	MED	12	92971	LED12D38W3827/40	120	6	5.31	1050	2300	2700	81	100W	25,000	Yes	★	Damp	Flood, 40° beam, White
			92972	LED12D38W3830/25	120	6	5.31	1050	5500	3000	81	100W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			92973	LED12D38WO3830/40	120	6	5.31	1050	2300	3000	80	100W	25,000	Yes	★	Wet	Flood, 40° beam, White
		18	92950	LED18D38OW3827/25	120	6	5.12	1550	5800	2700	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			92923	LED18D38W3927/25	120	6	5.31	1250	4900	2700	92	100W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			92958	LED18D38OW3827/40	120	6	5.12	1550	3800	2700	81	120W	25,000	Yes	★	Wet	Flood, 40° beam, White
			92926	LED18D38W3927/40	120	6	5.12	1250	2900	2700	92	120W	25,000	Yes	★	Damp	Flood, 40° beam, White
			92927	LED18D38W3930/15	120	6	5.32	1350	15000	3000	92	75W	25,000	Yes	★	Wet	Spot, 15° beam, White
			92961	LED18D38W3830/15	120	6	5.12	1750	20000	3000	81	150W	25,000	Yes	★	Wet	Spot, 15° beam, White
			92963	LED18D38OW3830/25	120	6	5.12	1550	6000	3000	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			92933	LED18D38W3930/25	120	6	5.31	1350	5200	3000	92	100W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			92967	LED18D38OW3830/40	120	6	5.12	1550	4000	3000	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White
			92934	LED18D38W3930/40	120	6	5.12	1350	3200	3000	92	120W	25,000	Yes	★	Damp	Flood, 40° beam, White
			85085	LED18D38OW3835/25	120	6	5.31	1700	6500	3500	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			87917	LED18D38OW3835/40	120	6	5.31	1700	4400	3500	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White
			93171	LED18D38OW3840/25	120	6	5.31	1700	6500	4000	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			93172	LED18D38OW3840/40	120	6	5.31	1700	4400	4000	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White
			65730	LED18D38OW3850/25	120	6	5.31	1700	6500	5000	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			65731	LED18D38OW3850/40	120	6	5.31	1700	4400	5000	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White

Directional Lamps (PAR38 – High Output)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Single Optics																	
		32	75447	LED32DP38W830/15	120	6	5.12	3000	26,000	3000	82	250W	25,000	Yes	★	Wet	Spot, 15° beam, White
			88801	LED32DP38W830/25	120	6	5.12	3000	13,000	3000	80	250W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			88810	LED32DP38W830/40	120	6	5.12	3000	6,000	3000	80	250W	25,000	Yes	★	Wet	Flood, 40° beam, White
			30233	LED32DP38W835/15	120	6	5.12	3100	25000	3500	80	250W	25,000	Yes	★	Wet	Spot, 15° beam, White
			30237	LED32DP38W835/25	120	6	5.12	3100	13000	3500	80	250W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			30239	LED32DP38W835/40	120	6	5.12	3100	6000	3500	80	250W	25,000	Yes	★	Wet	Flood, 40° beam, White

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

PERFORMANCE DATA ENERGY STAR® certified LED lamps

Directional Lamps (PAR30 - STIR)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Compact PAR30																	
PAR30	MED	12	98755	LED12DP303W83035	120	6	3.66	950	2600	3000	80	75W	25,000	Yes	★	Damp	Flood, 35˚ beam, White, STIR
Compact PAR30 Long Neck																	
PAR30L	MED	12	98811	LED12DP3L3W83035	120	6	4.61	950	2600	3000	80	75W	25,000	Yes	★	Damp	Accent, 35˚ beam, White, STIR

Directional Lamps (PAR30 - Low Glare - Visual Comfort Lens™)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Compact PAR30 - Low Glare - Visual Comfort Lens™																	
	MED	12	84374	LED12DP30RW93015	120	6	3.74	860	9400	3000	90	75W	25,000	Yes	★	Damp	Spot, 15° beam, White
			84379	LED12DP30RW93025	120	6	3.74	900	3900	3000	90	75W	25,000	Yes	★	Damp	Narrow Flood, 25˚ beam, White
			84380	LED12DP30RW93040	120	6	3.74	900	1800	3000	90	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			84392	LED12DP30RW92725	120	6	3.74	850	3500	2700	90	75W	25,000	Yes	★	Damp	Narrow Flood, 25˚ beam, White
			84395	LED12DP30RW92740	120	6	3.74	850	1700	2700	90	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			84384	LED12DP30RW83025	120	6	3.74	1050	4800	3000	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25˚ beam, White
			42131	LED12DP30RW83040	120	6	3.74	1050	2400	3000	80	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			42133	LED12DP30RW82725	120	6	3.74	1000	4700	2700	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25˚ beam, White
			42134	LED12DP30RW82740	120	6	3.74	1000	2200	2700	80	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			73583	LED12DP30RB82740	120	6	3.74	1000	2200	2700	80	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, Black
Compact PAR30 - Long Neck - Low Glare - Visual Comfort Lens™																	
	MED	12	84399	LED12DP3LRW93025	120	6	4.72	900	3900	3000	90	75W	25,000	Yes	★	Damp	Narrow Flood, 25˚ beam, White
			84400	LED12DP3LRW93040	120	6	4.72	900	1800	3000	90	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			84407	LED12DP3LRW92740	120	6	4.72	850	1700	2700	90	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			42136	LED12DP3LRW83025	120	6	4.72	1050	4800	3000	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25˚ beam, White
			42137	LED12DP3LRW83040	120	6	4.72	1050	2400	3000	80	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White
			42141	LED12DP3LRW82725	120	6	4.72	1000	4700	2700	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			42144	LED12DP3LRW82740	120	6	4.72	1000	2200	2700	80	75W	25,000	Yes	★	Damp	Flood, 40˚ beam, White

Directional Lamps (PAR16 - PAR20)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Compact PAR16																	
PAR16	MED	4	26383	LED4D/P16/NFLTP	120	3	2.8	260	720	3000	80	40W	25,000	Yes	★	Dry	Flood, 35° beam, White
		6	26384	LED6D/P16/NFLTP	120	3	2.8	380	1100	3000	80	60W	25,000	Yes	★	Dry	Flood, 35° beam, White
Compact PAR20																	
PAR20	MED	7	93327	LED7DP203B830/20	120	6	3.5	520	3600	3000	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam Black
			93347	LED7DP203W830/20	120	6	3.5	520	3600	3000	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam
			93348	LED7DP203W830/35	120	6	3.5	520	1200	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam
			93349	LED7DP203B827/20	120	6	3.5	500	3600	2700	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam Black
			93354	LED7DP203B827/35	120	6	3.5	500	1150	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam Black
			93360	LED7DP203W827/20	120	6	3.5	500	3600	2700	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam
			93362	LED7DP203W827/35	120	6	3.5	500	1150	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam

Reflector Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
BR30																	
	MED	10	68160	LED10DR303/827W	120	6	5.4	700		2700	80	65W	25,000	Yes	★	Damp	Frosted, White body
			68161	LED10DR303/830W	120	6	5.4	700		3000	80	65W	25,000	Yes	★	Damp	Frosted, White body
			69107	LED10DR303/850W	120	6	5.4	700		3000	80	65W	25,000	Yes	★	Damp	Frosted, White body
BR40																	
	MED	13	64176	LED13DBR40/827	120	6	6.3	1070		2700	80	85W	25,000	Yes	★	Damp	Frosted, White body
			14708	LED13DBR40/830	120	6	6.3	1070		3000	80	85W	25,000	Yes	★	Damp	Frosted, White body
			69108	LED13BR40/850	120	3	6.34	1070		5000	80	85W	25,000	Yes	★	Damp	Frosted, White body

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

ENERGY STAR® certified LED lamps

The benefits of an ENERGY STAR®-certified lamp are invaluable to our customers. ENERGY STAR® products have met a specific set of standards set up by the U.S. EPA and the U.S. Department of Energy, and can save customers money on their energy bills while also decreasing greenhouse gas emissions from power generation, all without sacrificing quality and style. Overall ownership costs can also be reduced by receiving lamp rebate incentives for eligible LED lamps from your local utility company.

Benefits

Benefits of a GE ENERGY STAR® certified LED lamp include:

- Uses about 75% less energy than a traditional incandescent lamp
- Lasts at least 6 times longer than an incandescent lamp
- Turns on instantly - there's no warm up time

Rebates

Rebates related to a GE ENERGY STAR® certified LED lamps can earn incentives...

- Up to $40 per lamp for lamps that meet individual utility eligibility requirements
- Contact your GE Lighting Sales Account Manager to learn more about rebates that may be available in your area. Go to **www.LED.com** for the most up-to-date listing of GE LED certified lamps
- This list is continually getting updated, please be sure to check the site often for the latest GE ENERGY STAR® certified LED lamp listing

LEARN MORE AT energystar.gov

Product is compliant with material restriction requirements of RoHS

ENERGY STAR® and the ENERGY STAR® logo are registered U.S. marks

current powered by GE

www.led.com

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions. © 2019 Current, powered by GE

65128 (Rev 08/13/19)