Lock system







Comfort handle AX

for compact enclosures AX with locking rod
Prepared for the installation of lock inserts or for the installation of standard commercially available 40 or 45 mm semi-cylinders, as well as lock and push-button inserts. The unlocked handle folds out forwards, and the lock is opened by swivelling.

Material:
– Die-cast zinc

Surface finish:
– Powder-coated

	 For lock inserts or semi-cylinders	 With security lock insert E1[1]	 For padlocks and lock inserts or semi-cylinders
	Model No.		
RAL 7035	**2435.100**	**2435.200**	**2435.400**
Lock inserts, type A			
7 mm square	2460.000	–	2460.000
8 mm square	2461.000	–	2461.000
7 mm triangular	2462.000	–	2462.000
8 mm triangular	2463.000	–	2463.000
Screwdriver	2464.000	–	2464.000
Daimler insert	2465.000	–	2465.000
3 mm double-bit	2466.000	–	2466.000
Fiat	2307.000	–	2307.000
6.5 mm triangular	2460.650	–	2460.650
Lock and push-button inserts			
Lock insert, lock no. 3524 E[2]	2467.000	–	2467.000
Push-button insert	2468.000	–	2468.000
Push-button and lock insert[2]	2469.000[3]	–	2469.000[3]
Semi-cylinders			
To DIN 18 252[4]	9785.040	–	9785.040
	9785.042[5]	–	9785.042[5]

[1] Only for use with VW, Audi, SEAT, Skoda Auto, supplied without key
[2] With two keys
[3] Lock no. 2123; no other lock is possible
[4] With 3 keys for each lock insert
[5] Packs of two, simultaneous locking within the same pack, no simultaneous locking for different packs