
C8R24835UNVW



UPC: 019813511221

Color: White

Weight: 1.9 lbs

Project:	Type:
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	0.22A
208V	0.13A
240V	0.11A
277V	0.097A
Input Watts	22.5W

LED Info

Watts	24W
Color Temp	3500K (Warm Neutral)
Color Accuracy	80 CRI
L70 Lifespan	50,000 Hours
Lumens	2,348
Efficacy	104.4 lm/W

Technical Specifications

Listings

UL Listed & UL Classified:

Suitable for wet locations

ENERGY STAR V2.2:

This product is ENERGY STAR® Version 2.2 Certified.

Energy Star Model Number:

DLC0009

Energy Star ID:

2350045

Electrical

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

THD:

<20%

Power Factor:

≥0.9

THDi:

Produces less than 20% THD

PF:

≥0.9

Input Voltage:

120V through 277V

Operating Frequency (Hz):

50/60Hz

Performance

Lifespan:

50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

Construction

IC Rated:

Suitable for direct contact with insulation.
Type IC inherently protected, suitable for direct contact to air permeable insulation and cULus listed for damp locations.
Not for use in direct contact with spray foam insulation, consult NEMA LSD57-2013.

Air Tight:

Housing certified Air Tight as per ASTM E283

Copyright © 2020 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

Construction

Housing:

Made from precision die-cast aluminum construction, dissipates heat from electrical components

Cold Weather Starting:

The minimum starting temperature is -30°C (-22°F)

Maximum Ambient Temperature:

Suitable for use in up to 40°C (104°F)

Green Technology:

Mercury and UV free. RoHS-compliant components.

Mounting:

Robust retention clips spring loaded tabs ensure the fixture is securely installed. Can be installed in 1/4" to 1 1/2" thick ceilings.

Lens:

Diffuse Polystyrene lens produces smooth uniform light that is glare free

Finish:

Matte White

Optical

Beam Angle:

90°±10°

LED Characteristics

LEDs:

Long-life, high-efficacy, surface-mount LEDs

Wattage Equivalency:

2 X 26W CFL

Flicker:

Silent and flicker free operations of less than 30%

Other

Template:

Template included for easy ceiling cut out

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Accessories:

DLPLATE/T: New Construction or Remodel Plate for T-Grid ceilings for use with 6" and 8" Models
DLPLATE/SJ: New Construction Plate for Stud/Joist mounting for use with 6" and 8" Models
DL8-10GOOF/R/P: 10" Goof Ring for 8" Commercial Downlight
DL8-12GOOF/R/P: 12" Goof Ring for 8" Commercial Downlight


Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	4	20.47	13.58	10.33
PALLET	224	9.94	9.94	85.04


Dimension



Copyright © 2020 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

C8R24835UNVW

Light Distribution



Features

- High Performance LEDs for commercial applications
- Replacement for traditional compact fluorescent recessed downlights
- Compatible with new construction or retrofit installations
- UL wet and Energy Star rated
- Meets air-tight requirements
- Matte white smooth trim finish
- Available in 3 color temperatures: 3000K, 3500K, 4000K
- 0 - 10V dimmable
- Spring loaded retention clips
- 25-inch Flexible conduit
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Size	Shape	Wattage	CRI/Color Temp	Voltage	Finish
C	8	R	24	835	UNV	W
	6 = 6" **8 =** 8"	**R =** Round	**12 =** 900lm-1050lm **18 =** 1500lm-1700lm **24 =** 2000lm-2300lm **33 =** 3000lm-3500lm	**940 =** 90 CRI, 4000K (Neutral) **935 =** 90 CRI, 3500K (Warm Neutral) **930 =** 90 CRI, 3000K (Warm) **840 =** 80 CRI, 4000K (Neutral) **835 =** 80 CRI, 3500K (Warm Neutral) **830 =** 80 CRI, 3000K (Warm)	**UNV =** 120-277V (0-10V Dimming)	**W =** White

Copyright © 2020 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice