


SKU: PDB-26-2/0-3

UPC: 0783669711202

Features & Benefits:

Description: Power Distribution Block, Dual Rated, Line Conductor Range 2/0-12, Load Range 2-14, 2 Ports Per Pole Line Side, 6 Ports Per Pole Load Side, 3 Pole, UL, CSA

Specs

Additional Class Attributes

Block Size	M
Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	8
Number of Poles	3
Number of Ports Per Pole Primary	2
Number of Ports Per Pole Secondary	6
Number of Ports / Wireways	24

Dimensions

Drive Size Main	3/16
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	Slotted
Height (IN)	2.625
Height BX (IN)	2.75
Length (IN)	4
Length (mm)	101.6
Mounting Hole Diameter (IN)	0.2
Mounting Hole Diameter (mm)	5.08
Mounting Hole Spacing (IN)	3.375
Mounting Hole Spacing (mm)	85.725
Weight (LB)	1.798
Weight BX (LB)	2.0658
Width (IN)	4.999
Width BX (IN)	5
Width (mm)	126.9746

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Enclosure Material	Valox
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366971120

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
ROHS Indicator	IND
RUS Listed	No
UL Control Number	NA
UL / CULUS Specification	UL 1059 Recognized
UL File Number	E84782

Color

Color	Black

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 12 Str
Conductor Range AL Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 12 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

Additional Technical Specifications

Connector Amperage Rating CU (Derated where applicable)	620 Amps
Conductor Type	Stranded

Voltage

Voltage Rating	600 V

Environment and Temperature

Flammability Rating	NA
Temperature Rating	90°C

nVent ILSCO
4701 Creek Rd, Suite 110
CINCINNATI, OH 45227
513-533-6200
800-776-9775