R6R8927120WB



UPC: 019813512747

Color: White

Weight: 0.8 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	0.07A
208V	N/A
240V	N/A
277V	N/A
Input Watts	7.7W

LED Info

Watts	8W
Color Temp	2700K
Color Accuracy	92 CRI
L70 Lifespan	50,000 Hours
Lumens	736 lm
Efficacy	90.625

Technical Specifications

Compliance

UL Classified:
Suitable for wet locations

Energy Star Approved:
ENERGY STAR® Version 2.2 Certified

Certification Model Number:
DLR0021

Energy Star ID:
2350014

NEC Compliant:
Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C5).

California Title 24:
Can be used to conform with the requirements of California Title 24 Part 6.

California Title 20 Compliant:
Compliant LED Product

Electrical

Dimming Driver:
TRIAC compatible dimmer with dimming as low as 5%. See dimmer compatibility guide here.

THD:
<20%

Power Factor:
≥0.9

THDi:
Produces less than 20% THD

PF:
≥0.9

Input Voltage:
120V

Flicker:
Silent and flicker free operations of less than 30%

Operating Frequency (Hz):
60Hz

Performance

Lifespan:
50,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations

Wattage Equivalency:
65W Incandescent

Construction

Shape:
Round

Trim Style:
Baffle

Housing:
Constructed from durable steel sheet metal

Cold Weather Starting:
The minimum starting temperature is -22°F (-30°C)

Maximum Ambient Temperature:
Suitable for use in up to 104°F (40°C)

Lens:
Frosted polycarbonate diffusion lens. Regressed lens. Constructed from durable sheet metal construction.

Green Technology:
Mercury and UV free. RoHS-compliant components.

Socket Adapter:
Edison 26 Medium Base Socket adapter included in box

Finish:
Matte White

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

Technical Specifications (continued)

LED Characteristics

Beam Angle:
95°±10°

LEDs:
Long-life, high-efficacy, surface-mount LEDs

R9 Value:
High color performance with R9 greater than or equal to 50

Installation

Mounting:
Easy installation with friction clips (4") and torsion springs (5"/6")

Other


Compatibility:
Compatible with most 5" and 6" recessed housings

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	4	15.47	7.99	8
PALLET	600	7.56	3.82	82.28


Dimension



Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

R6R8927120WB

Light Distribution



Features

- High Performance LEDS up to 100 lm/w
- Use to replace up to 100W traditional light sources
- Durable metal construction: dent and scratch resistant
- UL wet location rated
- Compatible with most standard recessed housings
- Dimmable down to 5% on compatible dimmers
- Available in Round 4" 850lm and 6" 850lm, 1050lm and 1400lm
- Available in 5 color temperatures: 2700K, 3000K, 3500K, 4000K, & 5000K
- Available in a smooth and baffle trim option
- Color designer trims as optional accessories available
- 5-Year, No-Compromise Warranty

Copyright © 2026 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice