Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure for Disconnect - 9851539

Date : May 27 , 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure for Disconnect - 9851539

created: 05.27.2021 build on https://www.rittal.us/



Product Description

Description	These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system foamed-in-place gasket and knife-edge sealing surface. Features include a cold rolled steel body and door and a zinc plated mounting panel.
Material	Door: Carbon steel all-round foamed-in PU seal Housing: Carbon steel Mounting plate: Carbon steel zinc-plated
Surface finish	Dipcoat-primed and powder-coated textured paint
Color	RAL 7035
Protection category IP to IEC 60 529	IP 66
Protection category NEMA:	NEMA 4
Supply includes	Mounting plate Housing with door(s) Left hand hinge Rear wall mounting holes Flange door with universal disconnect cutout
Dimensions	Height: 600 mm (24 ") Width: 650 mm (26 ") Depth: 250 mm (9.8 ")
Material thickness	Housing: 1.5 mm (0.06 ") Door: 2 mm (0.08 ") Mounting plate: 2.5 mm (0.1 ")

Mounting plate	Height: 570 mm (22 ") Width: 549 mm (22 ")
Packaging unit	1 pc(s).