

LED PAR20

5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB

Philips is driving the switch to energy-efficient solutions. Upgrade your track and accent lights with our small diameter reflectors for instant energy savings and unbeatable quality. Available in both Glass and Plastic casings, Philips LED Par20s are the ideal replacement for halogen.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	922-927 [CCT of 2200K-2700K]
Beam Angle (Nom)	40 degree(s)
Luminous Flux	500 lm
Luminous Intensity (Nom)	800 cd
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2200 2700 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5.5 W
Lamp Current (Nom)	54 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	75 °C

Controls and Dimming	
Dimmable	Only with specific dimmers

Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	PAR20 [PAR 2.5 inch/63mm]


Approval and Application	
Suitable For Accent Lighting	Yes
Energy Certifications	Energy Star

LED PAR20

Product Data	
Order product name	5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB
Full product name	5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB
Order code	929003026704
Material Nr. (12NC)	929003026704


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677568115
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677568110

Dimensional drawing




Product	D	C
5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB	64 mm	83.5 mm


Photometric data



Light Distribution Diagram - 5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB




Accent Lighting Spots - 5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB




Spectral Power Distribution Colour - 5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB

LED PAR20

Lifetime



Life Expectancy Diagram - 5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB



Lumen Maintenance Diagram - 5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.